













LED T5

- Designed to replace conventional fluorescent tubes
- Cost effective and energy saving
- Suitable for both switch start and high frequency
- Long life 30000 hours
- Low maintenance costs
- 3 Year Warranty
- Up to 49% Energy Savings



3 Year Silver Warranty				
Code	Lamp Type	Temp	Lm	ØxL (mm)
Non Dimmable				
04338	9W LED T5 HE Tube - G5, Non Dim, 549mm	4000K	950	20x549
04339	12W LED T5 HE Tube - G5, Non Dim, 849mm		1440	20x849
04340	16W LED T5 HE Tube - G5, Non Dim, 1149mm		2100	20x1149
04341	19W LED T5 HE Tube - G5, Non Dim, 1449mm		2500	20x1449
04343	25W LED T5 HO Tube - G5, Non Dim, 1449mm		3500	20x1449
04355	10W LED T5 Tube - HO -G5, Non Dim, 549mm		1600	20x549
04356	16W LED T5 Tube - HO - G5, Non Dim, 849mm		2400	20x849
04357	25W LED T5 Tube - HO - G5, Non Dim, 1149mm		3800	20x1149
For use with magnetic ballast: Remove starter and capacitor		-	-	-
For use with electronic ballast: Remove control gear and wire directly to mains		-	-	-

Energy Savings compared to old technology CFL Lamps

9W  14W  35% Energy Saving	10W  24W  58% Energy Saving	12W  21W  43% Energy Saving	16W  28W  43% Energy Saving	19W  35W  46% Energy Saving	25W  49W  49% Energy Saving
Quality Assured Product Warranty ³ 3 Year	Colour Rendering Index ² 85	Lumens Maintenance Ratio ¹ 80	Operating Hours 30,000		

