

LED CCT Wattage Switchable Integrated Batten

- Combines the reliability of the Ultra Batten with the added CCT & wattage switchable functionality
- 3000/4000/6000K Colour Switchable
- 4 Wattage Switchable
- Versatile general-purpose batten
- Plug in emergency pack, Microwave and PIR on/off sensors create a very stock friendly solution for wholesalers and contractors alike
- The ideal replacement for Single/Twin Fluorescent T8 and T5 Fixtures
- Special high light transmission frosted polycarbonate diffuser
- Tool-free termination
- Shatterproof
















Operating Hours 50,000

Efficiency Up To 170 Lm/W

Technical Specification	on
Construction	Steel Body, Polycarbonate lens
Driver	BELL
LED Chip	Samsung
Input Voltage	220 - 240V
Power Factor	> 0.9
Operating Temp	-30°C to +35°C / Emergency version min temp -5°C
Standard	CE & UKCA





Code	W	Description	Lm	Temp	LxHxD Fixings (mm)	
10278V2	22/27/33/40	LED Integrated Batten - CCT, 1200mm (4ft)	3418-7047	3/4/6000K		
06783	22/27/33/40	LED Integrated Batten - CCT, 1200mm (4ft) Microwave Corridor Dim	3418-7047	3/4/6000K	1170x70x61 900-955	
10279V2	32/40/47/60	LED Integrated Batten - CCT, 1500mm (5ft)	5006-10133	3/4/6000K	1470x70x61 1000-1055	
06784	32/40/47/60	LED Integrated Batten - CCT, 1500mm (5ft) Microwave Corridor Dim	5006-10133	3/4/6000K		
10280V2	46/54/67/80	LED Integrated Batten - CCT, 1800mm (6ft)	7150-13395	3/4/6000K	1755x70x61 1000-1055	
06785	46/54/67/80	LED Integrated Batten - CCT, 1800mm (6ft) Microwave Corridor Dim	7150-13395	3/4/6000K		
10281V2	-	Plug In Self-Test Selectable Emergency Pack for Ultra CCT Batten	-	-	-	
10282V2	-	Plug in Microwave Sensor On/Off for Ultra CCT Battens	-	-	-	
15197	-	Plug In On/Off PIR for Ultra CCT Batten	-	-	-	
08673	-	IR Remote Handset for 15197	-	-	-	
PIR Max O	perating Height	3.2m				
15197 Plud	In On/Off PIR	only compatible with 10278V2 / 10279V2 / 10280V2				