

LED Emergency Exit Blade

- Selectable Self Test or Manual Emergency Mode
- Sleek, low profile design
- Easy switching from non maintained to maintained via removable link
- Can be mounted to ceiling or wall
- Supplied with New Up Legend as standard
- Suitable for Commercial and Industrial installations
- Maintained / Non Maintained
- 25M Viewing Distance
- Viewable from both sides
- Recessing Kit option (Code 09048)




Product Warranty³
Including Battery
5 Year

Water & Dust
Protected
IP20


Self Test or
Manual Emergency
Mode

Operating
Hours
30,000


Technical Specification	
Construction	Polycarbonate
LED Chip	Samsung
Input Voltage	220 - 240V
Power Factor	> 0.9
Operating Temp	0°C to +35°C
Standard	CE & UKCA
Battery	LiFeP04



Surface Mounted Fitting



Recessed Fitting with 09048



Rotating fixing, can be mounted to ceiling or wall at 90° angle



5 Year Silver Warranty

Code	W	Description	Temp	Viewing Distance	WxHxD
09012V2	2.5	LED Emergency Exit Blade Surface including Up Legend. Maintained/Non Maintained	6500K	25M	310x230x35
09013	–	New Legend Left + Right for Exit Blade	–	–	–
09014	–	New Legend Down for Exit Blade	–	–	–
09015	–	New Legend Up for Exit Blade	–	–	–
09016	–	Old Legend Left + Right for Exit Blade	–	–	–
09017	–	Old Legend Down for Exit Blade	–	–	–
09018	–	Old Legend Up for Exit Blade	–	–	–
09048	–	Recessing kit for Emergency Surface Exit Blade	–	–	–

Legend Options



09013 New (ISO)
Left & right

09014 New (ISO)
Legend Down

09015 New (ISO)
Legend Up



09016 Old (Euro) Legend
Left & Right

09017 Old (Euro)
Legend Down

09018 Old (Euro)
Legend Up