




## LED Emergency High Power IP65 Twin Spot

- High efficiency upto 140lm/w
- Die cast spot head for enhanced heat dissipation
- Long life & low maintenance LifePO4 battery
- Suitable for M20 side conduit entry



Product Warranty <sup>3</sup> Including Battery	Water & Dust Protected	Mode	Impact Rating	Operating Hours
<b>5 Year</b>	<b>IP65</b>	<b>ST/Man EM</b>	<b>IK07</b>	<b>30,000</b>

Technical Specification	
Construction	Polycarbonate
LED Chip	Osram
Input Voltage	220 - 240V
Power Factor	> 0.9
Operating Temp	5°C to +55°C
Standard	CE & UKCA
Battery	LiFePO4



technical@belllighting.co.uk  
sales@belllighting.co.uk



### 5 Year Silver Warranty

Code	W	Description	Temp	Lm	HxWxD
09159	2 x7W	LED Emergency High Power IP65 Twin Spot	5500K	1965	280x280x75

**Note:** BELL Lighting is constantly developing and improving its products. For this reason, all product descriptions in this data sheet are intended as a general guide, and BELL lighting may change specifications from time to time in the interest of product development, without prior notification or public announcement. All descriptions in this data sheet present only general particulars of the goods to which they refer and shall not form part of any contract. Data in this guide has been obtained in controlled experimental conditions. However, BELL Lighting cannot accept any liability arising from the reliance on such data to the extent permitted.