

LED High Intensity UGR<20 High/Low Bay

- Perfect for sports hall, tennis, cricket or badminton
- Genuine replacement for 400W Metal Halide
- Ideal for racking, warehouse, large retail and factories
- TUV Isolated Driver
- 1-10V dimming as standard
- Suitable for High Bay and Low Bay applications 4-12m
- Plug in PIR & Microwave Sensors
- Sensor parameters set by remote control
- Emergency options available
- Self-Test options available
- Perfect for when low glare is required




50W \Rightarrow 100W  MH/SON Energy Saving 50%			100W \Rightarrow 250W  MH/SON Energy Saving 60%			200W \Rightarrow 400W  MH/SON Energy Saving 50%																				
Quality Assured Product Warranty ³ 7 Year			On site Warranty ³ 2 Year			Colour Rendering Index ³ 85			Lumens Maintenance Ratio ³ L80 B10			Water & Dust Protected IP65			Surge Protected 4000V			Impact Rating IK8			Low Unified Glare Rating UGR <20			Operating Hours 50,000		


Technical Specification	
Construction	Aluminium
Driver	Sosen
LED Chip	Seoul
Input Voltage	110-264V
Power Factor	> 0.9
Operating Temp	-30°C to +45°C / Emergency version min temp -5°C
Standard	CE & UKCA

Optional infra-red remote control available for microwave sensor versions.


Quick and easy adjustment for multiple fittings; dimming level, presence detection, light levels & automatic on-off time. Average 15M range




3 Step Dimming Function




With sufficient natural light, the fitting does not switch on when presence is detected.



With insufficient natural light, the sensor switches on automatically when presence is detected.



After the hold-time, the sensor dims the fitting to the pre-set low light level if no motion is detected.



Fitting switches off after the stand-by period has elapsed if no motion is detected.

7 Year Gold Warranty

Code	W	Description	Lm	Temp	Weight	LxHxD (mm)
11300	50	High Bay - Asymmetric	6692	4000K	2.3Kg	429x113x118
11301	50	High Bay - Symmetric	6860	4000K		
11302	50	High Bay - Emergency, Asymmetric	6692	4000K		
11303	50	High Bay - Emergency, Symmetric	6860	4000K		
11306	100	High Bay - Asymmetric	12876	4000K	4.1Kg	717x113x118
11307	100	High Bay - Symmetric	13764	4000K		
11308	100	High Bay - Emergency, Asymmetric	12876	4000K		
11309	100	High Bay - Emergency, Symmetric	13764	4000K		
11318	200	High Bay - Asymmetric,	25482	4000K	7.4Kg	1293x113x118
11319	200	High Bay - Symmetric	27388	4000K		
11320	200	High Bay - Emergency, Asymmetric	35482	4000K		
11321	200	High Bay - Emergency, Symmetric	27388	4000K		
08992	-	PIR for Illumina Linear UGR LED High Bay	-	-	-	-
08993	-	Microwave Sensor for Illumina Linear UGR LED High Bay	-	-	-	-
11324	-	Suspension Kit for Illumina Linear UGR LED High Bay	-	-	-	-
11325	-	60° Adjustable Bracket	-	-	-	-
06772	-	Remote Control for above sensor versions	-	-	-	-