



LED CCT Wallpack

- Genuine replacement for 70W Metal Halide & Sodium
- High impact polycarbonate construction
- 68% energy saving
- 30000 hours

Options

- Emergency version
- Photocell / Emergency Photocell version
- Microwave / Emergency Microwave version

CASAMBI



22W $\equiv$ 70W Energy Saving 68%

Quality Assured
Product Warranty²
3 Year

On site
Warranty²
1 Year

Colour Rendering
Index³
80

Lumens
Maintenance Ratio³
L80 B10


Water & Dust
Protected
IP65

Impact
Rating
IK8

Operating
Hours
30,000

Technical Specification

Construction	Polycarbonate Base & Lens
Driver	BELL
LED Chip	Samsung
Input Voltage	240V
Power Factor	> 0.9
Operating Temp	-30°C to +35°C / Emergency version min temp 0°C
Standard	CE & UKCA



technical@belllighting.co.uk
sales@belllighting.co.uk



3 Year Silver Warranty

Code	W	Description	Lm	Temp	Lm/W	Weight	WxHxD (mm)
11350	16/18/20/22	Muro CCT LED Wallpack	1255-1796	3/4/6000K	81	1.1Kg	255x305x101
11351		Muro CCT LED Wallpack Emergency		3/4/6000K			
11352		Muro CCT LED Wallpack Microwave Sensor		3/4/6000K			
11353		Muro CCT LED Wallpack Photocell		3/4/6000K			
11354		Muro CCT LED Wallpack Emergency Microwave Sensor		3/4/6000K			
11355		Muro CCT LED Wallpack - Emergency Photocell		3/4/6000K			