

Wattage Switchable LED High Bay

- Suitable for a wide range of industrial applications
- Streamline design
- 60-200 Wattage Switchable
- Seoul Semiconductor LED
- Plug-in PIR & Microwave sensors available
- Supplied with 1.5m flex
- Sensor parameters set by remote control
- Genuine Replacement for 250-600W Metal Halide or Sodium
- Perfect for warehousing, large retail and factories
- Emergency options
- Casambi versions available




100W \equiv 250W MH/SON Energy Saving 60% 150W \equiv 400W MH/SON Energy Saving 63% 200W \equiv 600W MH/SON Energy Saving 66%

| | | | | | | | |
|--|--|--|---|---------------------------------------|---------------------------------|------------------------------|----------------------------------|
| Quality Assured Product Warranty ¹ 7 Year | On site Warranty ² 2 Year | Colour Rendering Index ³ 85 | Lumens Maintenance Ratio ⁴ L80 B10 | Water & Dust Protected IP65 | Surge Protected 4000V | Impact Rating IK10 | Operating Hours 50,000 |
|--|--|--|---|---------------------------------------|---------------------------------|------------------------------|----------------------------------|

Technical Specification

| | |
|----------------|--|
| Construction | Die Cast Aluminium Body, Polycarbonate Lens |
| Driver | Muso 1-10V Dimmable as standard |
| LED Chip | Seoul Semiconductor |
| Input Voltage | 220-240V |
| Power Factor | > 0.9 |
| Operating Temp | -30°C to +50°C / Emergency version min temp -5°C |
| Standard | CE & UKCA |





Optional infra-red remote control available for PIR & microwave sensor versions.

Quick and easy adjustment for multiple fittings; dimming level, presence detection, light levels & automatic on-off time. Average 15M range.

7 Year Gold Warranty

| Code | W | Description | Lm | Temp | Weight | ØxH (mm) |
|-------|-------------|--|-------------|-------|--------|----------|
| 11450 | 60/80/100 | LED High Bay 120° lens | 9000-14000 | 4000K | 2Kg | 245x159 |
| 11451 | 60/80/100 | LED High Bay 90° lens | 9000-14000 | | | |
| 11452 | 90/120/150 | LED High Bay 120° lens | 14000-21000 | | 2.1Kg | 245x174 |
| 11453 | 90/120/150 | LED High Bay 90° lens | 14000-21000 | | | |
| 11454 | 120/160/200 | LED High Bay 120° lens | 18000-28000 | | 2.8Kg | 294x174 |
| 11455 | 120/160/200 | LED High Bay 90° lens | 18000-28000 | | | |
| 11478 | - | Emergency Pack | - | - | - | - |
| 11463 | - | Twist Microwave Sensor | - | - | - | - |
| 11464 | - | Twist PIR Sensor | - | - | - | - |
| 11465 | - | Casambi Bluetooth Wireless Node | - | - | - | - |
| 11522 | - | Polycarbonate Reflector for 60/80/100W and 90/120/150W | - | - | - | - |
| 11527 | - | Polycarbonate Reflector for 120/160/200W | - | - | - | - |
| 11523 | - | Aluminium Reflector for 60/80/100W | - | - | - | - |
| 11524 | - | Aluminium Reflector for 90/120/150W | - | - | - | - |
| 11526 | - | Aluminium Reflector for 120/160/200W | - | - | - | - |
| 11525 | - | Reflector Cover for 60/80/100W, 90/120/150W and 120/160/200W | - | - | - | - |
| 11429 | - | 30° Adjustable Bracket | - | - | - | - |
| 11466 | - | Remote Control for Illumina Atlas | - | - | - | - |