



LED Retrofit T5/T8 Magnetic T-Bar

- Retrofit solution for existing old T5/T8 installations
- Magnetic T-Bar attaches to existing fitting meaning there is no need for removal of existing fixtures
- Available in 4ft & 5ft
- Single & twin options
- Emergency options
- DALI as standard
- Includes separate driver



Quality Assured Product Warranty ¹	On site Warranty ²	Colour Rendering Index ³	Lumens Maintenance Ratio ⁴	Water & Dust Protected	Impact Rating	Operating Hours
5 Year	2 Year	85	L80 B10	IP20	IK6	50,000

Technical Specification	
Construction	Steel Body, Polycarbonate lens
Driver	Boke
LED Chip	Samsung
Input Voltage	220 - 240V
Power Factor	> 0.9
Operating Temp	-30°C to +35°C / Emergency version min temp -5°C
Standard	CE & UKCA



5 Year Silver Warranty

Code	W	Description	Lm	Temp	LxHxD (mm)
60920	15/20	T5/T8 Magnetic T-Bar - 4ft Single Pack	3000-3200	3/4000K	1129x27.5x27.5
60921	30/40	T5/T8 Magnetic T-Bar - 4ft Twin Pack	6000-6400	3/4000K	
60922	20/28	T5/T8 Magnetic T-Bar - 5ft Single Pack	4200-4480	3/4000K	1429x27.5x27.5
60923	40/56	T5/T8 Magnetic T-Bar - 5ft Twin Pack	8400-8960	3/4000K	-
60924	-	T5/T8 Magnetic T-Bar - Emergency Pack	-	-	-