
Aquaendure

Wattage Switchable CCT Vandal Resistant Anti Ligature LED Bulkhead

- Up to 174 lm/W
- CCT 3000K/4000K/6000K
- Genuine Replacement for 38W & 70W Bulkhead
- High impact polycarbonate lens
- Suitable for custodial and secure healthcare applications
- No lamp replacement
- Designed with safety as a priority


















Operating Hours

Technical Specificatio	chnical Specification		
Construction	Cast Aluminium + Polycarbonate		
Driver	BELL		
LED Chip	Samsung		
Input Voltage	220 - 240V		
Power Factor	> 0.9		
Operating Temp	-20°C to +40°C		
Standard	CE & UKCA		





10 Year Gold Warranty						
Code	W	Description	Lm	Temp	ØxH (mm)	
70035	18-36	Aqua Endure Anti Ligature Wattage Switchable LED Bulkhead - White		3/4/6000К	400x110	
70036	18-36	Aqua Endure Anti Ligature Wattage Switchable LED Bulkhead - White, Emergency Self Test On/Off Switch				
70037	28-36	Aqua Endure Anti Ligature Wattage Switchable LED Bulkhead - White, M/W Sensor Corridor Dim				
70038	28-36	Aqua Endure Anti Ligature Wattage Switchable LED Bulkhead - White, Emergency Self Test On/Off Switch, M/W Sensor Corridor Dim				
70039	18-36	Aqua Endure Anti Ligature Wattage Switchable LED Bulkhead - White, with 7W Nightlight (6-9W)				
70040	18	Aqua Endure Anti Ligature, LED Bulkhead - White, Dali	2847	7/4/60001/	400x110	
70029	36	Aqua Endure Anti Ligature, LED Bulkhead - White, Dali	6260	- 3/4/6000K		
*Lumens based	I on 4000K					