

## LED Bulkhead

- The ideal replacement for 16/28W 2D Fittings
- Tri level control now included on corridor dim versions
- Emergency option
- Microwave and corridor dimming function option
- High transmission frosted diffuser
- No lamp replacement
- No maintenance
- 30000 hour life
- IP65 Sealed fitting
- 8M detection range on corridor dim option (2.6m mounting height)



9W  16W **44%** Energy Saving

12W  28W **57%** Energy Saving

Quality Assured  
Product Warranty<sup>2</sup>  
**3 Year**

On site  
Warranty<sup>3</sup>  
**1 Year**

Colour Rendering  
Index<sup>1</sup>  
**85**


Lumens  
Maintenance Ratio<sup>1</sup>  
**L80 B10**

Water & Dust  
Protected  
**IP65**

Operating  
Hours  
**30,000**

### Technical Specification

Construction	Polycarbonate body and lens
Driver	BELL
LED Chip	Samsung
Input Voltage	220 - 240V
Power Factor	> 0.9
Operating Temp	-20°C to +40°C
Standard	CE & UKCA





With sufficient natural light, the fitting does not switch on when presence is detected.



With insufficient natural light, the sensor switches on automatically when someone enters the room.



When the room is empty, light dims to stand-by level (10% / 20% / 30%) after the hold-time.



Light switched off automatically after the stand-by period has elapsed.

### 3 Year Silver Warranty

Code	W	Description	Lm	Temp	ØxH (mm)
70050	9	Genesis 9W Bulkhead	1130	4000K	240x75
70051	9	Genesis 9W Bulkhead Emergency			
70052	9	Genesis 9W Bulkhead Sensor On/Off			
70053	9	Genesis 9W Bulkhead Emergency Sensor On/Off			
70054	9	Genesis 9W Bulkhead Sensor Dim			
70055	9	Genesis 9W Bulkhead Emergency Sensor Dim	1380	4000K	280x78
70056	12	Genesis 12W Bulkhead			
70057	12	Genesis 12W Bulkhead Emergency			
70058	12	Genesis 12W Bulkhead Sensor On/Off			
70059	12	Genesis 12W Bulkhead Emergency Sensor On/Off			
70060	12	Genesis 12W Bulkhead Sensor Dim			
70061	12	Genesis 12W Bulkhead Emergency Sensor Dim			

Microwave Max Operating Height 3.2m