



Wattage Switchable CCT LED Wallpack

- Asymmetric light distribution to reduce light spill
- CCT 3/4/6000K
- 4 wattage Switchable
- Genuine replacement for 70W Metal Halide & Sodium
- TUV Certified Driver
- High impact polycarbonate lens
- 65% energy saving
- 50000 hours

Options

- Standard
- Photocell
- Emergency
- Emergency Photocell

CASAMBI



24W  70W **65%** Energy Saving

Quality Assured
Product Warranty¹
7 Year

On site
Warranty²
2 Year

Colour Rendering
Index³
80

Lumens
Maintenance Ratio⁴
L80 B10

Water & Dust
Protected
IP65

Impact
Rating
IK8

Operating
Hours
50,000

Technical Specification

Construction	Aluminium Base Polycarbonate Lens
Driver	Boak
LED Chip	Samsung
Input Voltage	220/240V
Power Factor	> 0.9
Operating Temp	-30°C to +35°C / Emergency version min temp 0°C
Standard	CE & UKCA



7 Year Gold Warranty

Code	W	Description	Lm	Temp	Lm/W	Weight	WxHxD (mm)
70120	14/17/21/24	Wattage Switchable Asymmetric CCT LED Wallpack	1781-3241	3/4/6000K	122-157	1.15Kg	162x309x217
70121	14/17/21/24	Wattage Switchable Asymmetric CCT LED Wallpack- Emergency	1781-3241	3/4/6000K	122-157		
70122	14/17/21/24	Wattage Switchable Asymmetric CCT LED Wallpack - Photocell	1781-3241	3/4/6000K	122-157		
70123	14/17/21/24	Wattage Switchable Asymmetric CCT LED Wallpack - Emergency Photocell	1781-3241	3/4/6000K	122-157		
70124	14/17/21/24	Wattage Switchable Symmetric CCT LED Wallpack	1702-3071	3/4/6000K	118-134		
70125	14/17/21/24	Wattage Switchable Symmetric CCT LED Wallpack- Emergency	1702-3071	3/4/6000K	118-134		
70126	14/17/21/24	Wattage Switchable Symmetric CCT LED Wallpack - Photocell	1702-3071	3/4/6000K	118-134		
70127	14/17/21/24	Wattage Switchable Symmetric CCT LED Wallpack - Emergency Photocell	1702-3071	3/4/6000K	118-134		