




LED Wattage Switchable CCT Bulkhead

- CCT 3000/4000/5000/6000K
- 3 Wattage Switchable 9/12/16W
- Hinged LED gear tray for ease of maintenance
- Twist & Lock diffuser mechanism
- Impact resistant polycarbonate lens with high transmission frosted diffuser
- Available with Plug in Emergency Pack with Self Test Switch & Microwave Sensor (Optional)
- Sensor built-in with both On/Off & Corridor Dim functionality
- 8M detection range on corridor dim option (2.6m mounting height)
- Rear, Side & BESA Box, suitable for M20 Conduit entry
- Black Bezel & White/Black Eyelids available



Technical Specification	
Construction	Polycarbonate body and lens
Driver	BELL
LED Chip	Samsung
Input Voltage	220 - 240V
Power Factor	> 0.9
Operating Temp	-20°C to +40°C - Emergency version min temp -5°C
Standard	CE & UKCA



technical@belllighting.co.uk
sales@belllighting.co.uk



7 Year Gold Warranty

Code	W	Description	Lm	Temp	ØxH (mm)
70200	9/12/16	4 CCT Wattage Switchable Bulkhead	1080-2240	3/4/5/6000K	325x75
70201	-	Self-Test Selectable Emergency Pack for Aqua Connect	-	-	-
70202	-	Aqua Connect Plug in Dual On/Off & Corridor Dim Sensor	-	-	-
70203	-	IR Remote Handset for 70202	-	-	-
70204	-	White Eyelid for above	-	-	-
70205	-	Black Eyelid for above	-	-	-
70206	-	Black Bezel for above	-	-	-