

LED Wattage CCT Switchable High Bay

- High efficiency highbay upto 200lm/w with high power LEDs
- Upto 6 Wattage selectable 200W, 180W, 160W, 140W, 120W & 100W
- Enhanced user comfort with excellent glare control upto UGR<22
- Excellent heat dissipation through "Coanda effect" product design aiding in less dust collection as well.
- Embedded Zhaga Socket for easy adaptability with sensor control & wireless integration
- Available in 120deg & 90deg beam angle lens
- Available with DALI or Casambi integration (optional)
- Mounting bracket option available



6 Wattage Select



Zhaga Socket



Quality Assured
Product Warranty¹
7 Year

On site
Warranty²
2 Year*

Colour Rendering
Index²
80

Lumens
Maintenance Ratio¹
L80 B10

Water & Dust
Protected
IP66

Impact
Rating
IK08

Operating
Hours
100,000

Technical Specification

Construction	ADC12 Die-cast aluminium
Driver	Integral
LED Chip	LiteON SMD5050
Input Voltage	220-240V
Power Factor	> 0.9
Operating Temp	-40°C to +50°C
Standard	CE & UKCA



7 Year Gold Warranty

Code	W	Description	Lm	Temp	Weight	ØxH (mm)
70370		Illumina Elite 2 LED Highbay - 120° Lens	20000-40000			
70371	200/180/160/	Illumina Elite 2 LED Highbay - 90° Lens	20000-40000	4000K	2.7Kg	390x91
70372	140/120/100	Illumina Elite 2 LED Highbay - 120° Lens, DALI	20000-40000			
70373		Illumina Elite 2 LED Highbay - 90° Lens, DALI	20000-40000			