



Foxbridgesensor

IP44 Wall Mount PIR Sensor

- Adjustable head - both vertically & horizontally
- Adjustable ambient light & time delay settings.
- Suitable for semi-outdoor applications like patio, utility corridors, staircases
- Detection moving speed from 0.6-1.5ms



Installation Height: 1.8m-2.5m



Detection Distance: Max. 12m

5 Year Silver Warranty

Code	Description	HxWxD (mm)
70401	IP44 Wall Mount PIR Sensor - White	70x55x77
70402	IP44 Wall Mount PIR Sensor - Black	

Quality Assured Product Warranty ¹	Water & Dust Protected	Sensing	Mounting Options
5 Year	IP44	PIR	Wall

Technical Specification	
Construction	Polycarbonate Flame Retardant Body
Input Voltage	200-220 VAC
Frequency	50/60 Hz
Operating Temp	-20°C to +40°C
Load Capacity	LED 400W Halogen 800W
Time Delay	10s-7m
Lux Settings	<10-2000Lux
Protection Class	Class II
Compliance	EN 60669-2-1
Standard	LVD directive 2014/35/EU EMC directive 2014/30/EU

Note: BELL Lighting is constantly developing and improving its products. For this reason, all product descriptions in this data sheet are intended as a general guide, and BELL lighting may change specifications from time to time in the interest of product development, without prior notification or public announcement. All descriptions in this data sheet present only general particulars of the goods to which they refer and shall not form part of any contract. Data in this guide has been obtained in controlled experimental conditions. However, BELL Lighting cannot accept any liability arising from the reliance on such data to the extent permitted.