



Foxbridgesensor

IP44 Wall Mount PIR Sensor

- Adjustable head - both vertically & horizontally
- Adjustable ambient light & time delay settings.
- Suitable for semi-outdoor applications like patio, utility corridors, staircases
- Detection moving speed from 0.6-1.5ms



Installation Height: 1.8m-2.5m



Detection Distance: Max. 12m

5 Year Silver Warranty

| Code | Description | HxWxD (mm) |
|-------|------------------------------------|------------|
| 70401 | IP44 Wall Mount PIR Sensor - White | 70x55x77 |
| 70402 | IP44 Wall Mount PIR Sensor - Black | |

| | | | |
|---|------------------------|------------|------------------|
| Quality Assured Product Warranty ¹ | Water & Dust Protected | Sensing | Mounting Options |
| 5 Year | IP44 | PIR | Wall |

| Technical Specification | |
|-------------------------|---|
| Construction | Polycarbonate Flame Retardant Body |
| Input Voltage | 200-220 VAC |
| Frequency | 50/60 Hz |
| Operating Temp | -20°C to +40°C |
| Load Capacity | LED 400W Halogen 800W |
| Time Delay | 10s-7m |
| Lux Settings | <10-2000Lux |
| Protection Class | Class II |
| Compliance | EN 60669-2-1 |
| Standard | LVD directive 2014/35/EU EMC directive 2014/30/EU |

Note: BELL Lighting is constantly developing and improving its products. For this reason, all product descriptions in this data sheet are intended as a general guide, and BELL lighting may change specifications from time to time in the interest of product development, without prior notification or public announcement. All descriptions in this data sheet present only general particulars of the goods to which they refer and shall not form part of any contract. Data in this guide has been obtained in controlled experimental conditions. However, BELL Lighting cannot accept any liability arising from the reliance on such data to the extent permitted.