





# Foxbridgesensor

## IP65 Wall/Ceiling Mount PIR Sensor

- Adjustable head - angle of the detector head adaptable to on-site environment
- Ease of Maintenance - the lux & time settings can be changed using potentiometers
- Versatile mounting options - ceiling and wall
- Wide detection angle upto 180°



Installation Height: 1.8m-2.5m



Detection Distance: Max. 12m

5 Year Silver Warranty		
Code	Description	HxWxD (mm)
70403	IP65 Wall/Ceiling Mount PIR Sensor - White	130x80x40
70404	IP65 Wall/Ceiling Mount PIR Sensor - Black	

Quality Assured  
Product Warranty<sup>3</sup>  
**5 Year**

Water & Dust  
Protected  
**IP65**

Sensing  
**PIR**

Mounting  
Options  
**Wall/Ceiling**

Technical Specification	
Construction	Polycarbonate Flame Retardant Body
Input Voltage	200-220 VAC
Frequency	50/60 Hz
Operating Temp	-20°C to +40°C
Load Capacity	LED 300W Halogen 1200W
Time Delay	10s-15m
Lux Settings	<3-2000Lux
Protection Class	Class II
Compliance	EN 60669-2-1
Standard	LVD directive 2014/35/EU EMC directive 2014/30/EU

**Note:** BELL Lighting is constantly developing and improving its products. For this reason, all product descriptions in this data sheet are intended as a general guide, and BELL lighting may change specifications from time to time in the interest of product development, without prior notification or public announcement. All descriptions in this data sheet present only general particulars of the goods to which they refer and shall not form part of any contract. Data in this guide has been obtained in controlled experimental conditions. However, BELL Lighting cannot accept any liability arising from the reliance on such data to the extent permitted.