

Foxbridgesensor

IP20 Surface Mount PIR Sensor with Adjustable Detection Range



- Wide detection range - the walk across detection upto 12m
- Tailored detection zone - The detection area can be adapted using the detection shields
- Detection moving speed 0.6-1.5ms
- Easy to adjust Lux & time delay settings



Surface Mount



Installation Height: 2.2m-4m



Detection Distance: Max. 12m

5 Year Silver Warranty

Code	Description	ØxD (mm)
70405	IP20 Surface Mount PIR Sensor with Adjustable Detection Range	80x38

Quality Assured Product Warranty ¹	Water & Dust Protected	Sensing	Mounting Options
5 Year	IP20	PIR	Surface

Technical Specification	
Construction	Polycarbonate Flame Retardant Body
Input Voltage	200-220 VAC
Frequency	50/60 Hz
Operating Temp	-20°C to +40°C
Load Capacity	LED 300W Halogen 1200W
Time Delay	10s-7m
Lux Settings	<10-2000Lux
Protection Class	Class II
Compliance	EN 60669-2-1
Standard	LVD directive 2014/35/EU EMC directive 2014/30/EU

Note: BELL Lighting is constantly developing and improving its products. For this reason, all product descriptions in this data sheet are intended as a general guide, and BELL lighting may change specifications from time to time in the interest of product development, without prior notification or public announcement. All descriptions in this data sheet present only general particulars of the goods to which they refer and shall not form part of any contract. Data in this guide has been obtained in controlled experimental conditions. However, BELL Lighting cannot accept any liability arising from the reliance on such data to the extent permitted.