

Foxbridgesensor

IP54 Nema Photocell Sensor

- Suitable for NEMA 3-Pin socket installation
- Suitable for daylight harvesting with auto control of switching
- Easy to install - Wall mounted
- High capacity load control upto 10A.



5 Year Silver Warranty

Code	Description	Dimensions (mm)
70408	IP54 Nema Photocell Sensor	130/79/86

Quality Assured Product Warranty ¹ 5 Year	Water & Dust Protected IP54	Sensing Photocell	Mounting Options Wall
---	--	-----------------------------	------------------------------------

Technical Specification	
Construction	Polycarbonate Flame Retardant Body
Input Voltage	200-220 VAC
Frequency	50/60 Hz
Operating Temp	-20°C to +40°C
Load Capacity	Upto 10A
Lux Settings	<10Lux (ON) / >40Lux (OFF)
Protection Class	Class II
Compliance	EN 60669-2-1
Standard	LVD directive 2014/35/EU EMC directive 2014/30/EU

Note: BELL Lighting is constantly developing and improving its products. For this reason, all product descriptions in this data sheet are intended as a general guide, and BELL lighting may change specifications from time to time in the interest of product development, without prior notification or public announcement. All descriptions in this data sheet present only general particulars of the goods to which they refer and shall not form part of any contract. Data in this guide has been obtained in controlled experimental conditions. However, BELL Lighting cannot accept any liability arising from the reliance on such data to the extent permitted.