

# Skylinevirtus CCT

## Asymmetric/Symmetric CCT switchable, in-built photocell with on/off LED Floodlight

- Wattage (3 settings) & CCT (3000K/4000K/5000K) switchable
- Up to 185 lm/W
- Aerodynamic, streamlined design for reduced windage
- Available with high output, high efficiency asymmetric light distribution for low light pollution (Asymmetric version only)
- Additional visors available (optional)
- C5-M Marine Grade treated construction suitable for coastal areas & harsh environments
- Built in photocell with manual override on/off switch
- Supplied pre-wired 1.5m cable
- Suitable for Sports Lighting, Facade Lighting, Area Lighting, & Open Car parks
- Suitable for Site Lighting 110 VAC




Contact Customer Service for CASAMBI & DALI options



100W  $\approx$  250 W MH/SON 60% Energy Saving  
 200W  $\approx$  500 W MH/SON 60% Energy Saving

Quality Assured Product Warranty <sup>2</sup> <b>8 Year</b>	On site Warranty <sup>2</sup> <b>2 Year</b>	Colour Rendering Index <sup>2</sup> <b>80</b>	Lumens Maintenance Ratio <sup>1</sup> <b>L80 B10</b>	Water & Dust Protected <b>IP66</b>	Impact Rating <b>IK08</b>	Operating Hours <b>100,000</b>	Suitable For Site Lighting <b>110V</b>	Surge Protected <b>10000V</b>
--	--	--	---	---------------------------------------	------------------------------	-----------------------------------	---	----------------------------------

Technical Specification	
Construction	Polyester coated die-cast LM6 Marine Grade aluminium & toughened safety glass
Driver	LiFud 0-10V Dimmable
LED Chip	Nichia GRT-V1
Input Voltage	110 - 240V
Power Factor	> 0.9
Operating Temp	-30°C - +45°C
Standard	CE & UKCA



technical@belllighting.co.uk  
 sales@belllighting.co.uk



### 8 Year Gold Warranty

Code	W	Description	Lm	Temp	Lm/W	Weight	Windage	WxHxD (mm)
70470	50/75/100	LED Floodlight CCT, Asymmetric Photocell with On/Off	8000-16800	3/4/5000K	150-172	2.7Kg	0.09m <sup>2</sup> at 90°	277x358x53
70471	100/150/200	LED Floodlight CCT, Asymmetric Photocell with On/Off	15500-33000	3/4/5000K	145-170	4Kg	0.12m <sup>2</sup> at 90°	322x421x53
70472	150/225/300	LED Floodlight CCT, Asymmetric Photocell with On/Off	24000-49500	3/4/5000K	140-178	4.9Kg	0.14m <sup>2</sup> at 90°	363x443x53
70473	50/75/100	LED Floodlight CCT, Symmetric Photocell with On/Off	8350-17600	3/4/5000K	157-181	2.7Kg	0.09m <sup>2</sup> at 90°	277x358x53
70474	100/150/200	LED Floodlight CCT, Symmetric Photocell with On/Off	16100-34200	3/4/5000K	150-176	4Kg	0.12m <sup>2</sup> at 90°	322x421x53
70475	150/225/300	LED Floodlight CCT, Symmetric Photocell with On/Off	24900-51300	3/4/5000K	145-185	4.9Kg	0.14m <sup>2</sup> at 90°	363x443x53