

Skylinevirtus CCT

Asymmetric/Symmetric CCT switchable, in-built photocell with on/off LED Floodlight

- Wattage (3 settings) & CCT switchable 3000K/4000K/5000K
- Available with high output, high efficiency asymmetric light distribution for low light pollution (Asymmetric version only)
- C5-M Marine Grade treated construction suitable for coastal areas & harsh environments
- Suitable for Sports Lighting, Facade Lighting, Area Lighting, & Open Car parks
- Aerodynamic, streamlined design for reduced windage
- Built in photocell with manual override on/off switch
- Additional visors available (optional)
- Suitable for Site Lighting 110 VAC
- Supplied pre-wired 1.5m cable
- Up to 185lm/W



Contact Customer Service for CASAMBI & DALI options



100W \approx 250 W MH/SON Energy Saving 60%
200W \approx 500 W MH/SON Energy Saving 60%

Quality Assured
Product Warranty²
8 Year

On site
Warranty²
2 Year

Colour Rendering
Index²
80

Lumens
Maintenance Ratio²
L80 B10

Water & Dust
Protected
IP66

Impact
Rating
IK08


Operating
Hours
100,000

Suitable For
Site Lighting
110V

Surge
Protected
10000V

Technical Specification

Construction	Polyester coated die-cast LM6 Marine Grade aluminium & toughened safety glass
Driver	SOSEN
LED Chip	Nichia GRT-V1
Input Voltage	110 - 240V
Power Factor	> 0.9
Operating Temp	-30°C - +45°C
Standard	CE & UKCA



technical@belllighting.co.uk
sales@belllighting.co.uk



8 Year Gold Warranty

Code	W	Description	Lm	Temp	Lm/W	Weight	Windage	WxHxD (mm)
70470	50/75/100	LED Floodlight CCT, Asymmetric Photocell with On/Off	8000-16800	3/4/5000K	150-172	2.7Kg	0.09m ² at 90°	277x358x53
70471	100/150/200	LED Floodlight CCT, Asymmetric Photocell with On/Off	15500-33000	3/4/5000K	145-170	4Kg	0.12m ² at 90°	322x421x53
70472	150/225/300	LED Floodlight CCT, Asymmetric Photocell with On/Off	24000-49500	3/4/5000K	140-178	4.9Kg	0.14m ² at 90°	363x443x53
70473	50/75/100	LED Floodlight CCT, Symmetric Photocell with On/Off	8350-17600	3/4/5000K	157-181	2.7Kg	0.09m ² at 90°	277x358x53
70474	100/150/200	LED Floodlight CCT, Symmetric Photocell with On/Off	16100-34200	3/4/5000K	150-176	4Kg	0.12m ² at 90°	322x421x53
70475	150/225/300	LED Floodlight CCT, Symmetric Photocell with On/Off	24900-51300	3/4/5000K	145-185	4.9Kg	0.14m ² at 90°	363x443x53
70477	-	50/75/100W 360° visor	-	-	-	-	-	-
70478	-	100/150/200W 360° visor	-	-	-	-	-	-
70479	-	150/225/300 360° visor	-	-	-	-	-	-