

LED BLD/BLT/BLL/BLS Glass

- Familiar look and feel of classic CFL lamps but with all the benefits of LED
- Energy saving benefits of LED without having to change fittings
- Aluminium heat sink for improved life
- True retrofit size
- Not suitable for emergency or dimming
- Suitable for switch start/magnetic control gear
- Must bypass High Frequency control gear



3 Year Silver Warranty				
Code	Lamp Type	Temp	Lm	HxW (mm)
Non Dimmable				
71014	3W LED Glass BLS 2 Pin - G23, 360°	2700K	360	137x30
71000	3W LED Glass BLS 2 Pin - G23, 360°	4000K	360	
71015	5W LED Glass BLS 2 Pin - G23, 360°	2700K	680	220x30
71001	5W LED Glass BLS 2 Pin - G23, 360°		700	
71002	5W LED Glass BLS 4 Pin - 2G7, 360°		700	116x34
71003	4.5W LED Glass BLD 2/4 Pin - G24, 360°		580	
71004	6W LED Glass BLD 2/4 Pin - G24, 360°		835	148x34
71005	9W LED Glass BLD 2/4 Pin - G24, 360°		1300	171x34
71006	6W LED Glass BLT 2/4 Pin - GX24, 360°	4000K	835	125x50
71007	9W LED Glass BLT 2/4 Pin - GX24, 360°		1300	145x50
71008	10W LED Glass BLT 2/4 Pin - GX24, 360°		1375	
71009	13W LED Glass BLT 2/4 Pin - GX24, 360°		1780	167x50
71010	8W LED Glass BLL 4 Pin - 2G11, 360°		1000	230x44
71011	12W LED Glass BLL 4 Pin - 2G11, 360°		1475	325x44
71012	18W LED Glass BLL 4 Pin - 2G11, 360°		2250	417x44
71013	24W LED Glass BLL 4 Pin - 2G11, 360°		3200	537x44

For use with magnetic ballast: Remove starter and capacitor
 For use with electronic ballast: Remove control gear and wire directly to mains
 Not suitable for emergency

Energy Savings compared to old technology CFL Lamps



Quality Assured Product Warranty ³ 3 Year	Colour Rendering Index ⁴ 80	Lumens Maintenance Ratio ⁵ 80	Operating Hours 25,000
--	--	--	----------------------------------

