

LED BLD/BLT/BLL/BLS

- Energy saving benefits of LED without having to change fittings
- Aluminium heat sink for improved life
- Thermoplastic for improved durability
- 180° light distribution
- True retrofit size
- High CRI
- Suitable for switch start/magnetic control gear
- Must bypass High Frequency control gear



5 Year Silver Warranty

Code	Lamp Type	Temp	Lm	HxW (mm)
Non Dimmable				
70080	3.5W LED BLS 2 Pin - G23	4000K	350	135x32
70081	6W LED BLS 2 Pin - G23		600	237x32
70082	7W LED BLD 2/4 Pin - G24d/q		700	148x35
70083	9W LED BLD 2/4 Pin - G24d/q		900	171x35
70084	7W LED BLT 2/4 Pin - GX24d/q		700	124x38
70085	9W LED BLT 2/4 Pin - GX24d/q		900	139x38
70088	13W LED BLT 2/4 Pin - GX24d/q		1800	162x49
70089	15W LED BLT 2/4 Pin - GX24d/q		2250	172x49
70086	10W LED BLL 4 Pin - 2G11		1000	327x44
70087	18W LED BLL 4 Pin - 2G11		1800	542x44
71020	3.5W LED BLS 2 Pin - G23	3/4/6000K	350	135x32
71021	6W LED BLS 2 Pin - G23		600	220x32
71022	7W LED BLD 2/4 Pin - G24d/q		700	148x35
71023	9W LED BLD 2/4 Pin - G24d/q		900	171x35
71024	7W LED BLT 2/4 Pin - GX24d/q		700	132x37
71025	9W LED BLT 2/4 Pin - GX24d/q		900	147x37
71028	13W LED BLT 2/4 Pin - GX24d/q		1800	162x49
71029	15W LED BLT 2/4 Pin - GX24d/q		2250	172x49
71026	10W LED BLL 4 Pin - 2G11		1000	327x44
71027	18W LED BLL 4 Pin - 2G11		1800	542x44
09125	Emergency Pack for above - Self Test On/Off Switch	-	-	-
For use with magnetic ballast: Remove starter and capacitor				
For use with electronic ballast: Remove control gear and wire directly to mains				

Energy Savings compared to old technology CFL Lamps

