BELLlighting

Anna



## LED Emergency IP65 Twin Spot

The Spectrum IP65 Twin Spot is IP65 as standard. Supplied as both Self Test & Non Self Test, with 20mm side & rear entry and a 5 year warranty.

- Selectable Self Test or Manual Emergency Mode
- Long life & low maintenance
- Compact design & robust construction
- 20mm Side & rear entry




Auto Self Test Indicator. No requirement for manual key test (when switched to self test operation). Normal operation: Green indicator illuminated Battery failure: Red indicator: Single Flash Light source failure: Red: Double Flash Less than rated duration time: Red: Triple Flash

Technical Specifica	tion			
Construction	Polycarbonate			
LED Chip	Samsung			
IP Rating	IP65			
Operating Temp	0°C to +35°C			
Input Voltage	220 - 240V			
Power Factor	> 0.9			
Battery	LiFePO4			
Code W E	escription	Temp	Lm	Hours

Code	W	Description	Temp	Lm	Hours
09088V2	12	LED Emergency Twin Spot IP65. Non Maintained - White	6500K	550	30000
09128	12	LED Emergency Twin Spot IP65. Non Maintained - Black	6500K	550	30000

See end of Emergency Lighting section for spacing tables

Must be tested in line with the requirements of BS5266, failure to do so may effect battery life and warranty.



technical@belllighting.co.uk sales@belllighting.co.uk

Product

Upgrade