

BELLlighting

260










LED Emergency Bulkhead / Recessed

Our most popular emergency bulkhead, the 3.3W IP65 bulkhead has a low-profile design and is suitable for both internal ϑ external use. The optional exit blade accessory transforms this Emergency Bulkhead into an IP65 Exit Blade.

- Selectable Self Test or Manual Emergency Mode
- 3.3W IP65 Bulkhead
- Low profile slim design
- Long life
- Low maintenance
- Includes full set of New Legends
- Old Legends also available
- Internal/external use
- Viewing distance 25M
- Daylight 6500K
- 20mm Conduit entry
- Hinged Gear Tray for easy install
- Tool-Free termination
- 09046 Exit Blade Accessory available, when fitted this adapts 3.3W Bulkheads in to cost effective IP65 Exit Blades.





Cut Out: 350mm x 110mm When used with Semi Recessing Kit (09041) Ceiling Mounted Fitting



Recessed Fitting



LED Emergency Bulkhead / Recessed



▌←⋩ ⋞→▋ ⋞↓∎ ⋞↑∎

09043 Old (Euro) Legends Kit

Technical Specification					
Construction		Polycarbonate			
LED Chip		Samsung			
IP Rating		IP65			
Operating Temp		0°C to +35°C			
Input Voltage		220 - 240V			
Power Factor		> 0.9			
Battery		LiFePO4			
Code	W	Description	Temp	Lm	Hours
09040V2	3.3	LED Emergency Bulkhead IP65. Maintained/Non Maintained Includes set of 4 New Legends	6500K	190	25000
09041	-	Semi Recessing Kit for LED Emergency Bulkhead	-	-	-
09043	-	Old Legend Kit for Emergency Bulkhead (Set of 4)	-	-	-
09046	-	Exit Blade Accessory			

See end of Emergency Lighting section for spacing tables

Must be tested in line with the requirements of BS5266, failure to do so may effect battery life and warranty.

technical@belllighting.co.uk sales@belllighting.co.uk

III

.....

1- 2

MIN

A

ICO