

BELLlighting

252



www.belllighting.co.uk

Spectrum



Recessed Downlights

The 3W Spectrum Non Maintained Downlights have a dual colour charge indicator and come complete with a battery pack enclosed in a protective housing. This IP20 rated fixture can be purchased for both Open Area and Corridor applications.

- Selectable Self Test or Manual Emergency Mode
- Open Area / Corridor versions
- Dual colour charge indicator
- Complete with driver and fire rated battery pack
- 3W recessed

09030V2

09031V2

3

3



| Technical Specification | | | | | |
|-------------------------|---------------|--|------|----|-------|
| Construction | Polycarbonate | | | | |
| LED Chip | Samsung | | | | |
| IP Rating | IP20 | | | | |
| Operating Temp | 0°C to +35°C | | | | |
| Input Voltage | 220 - 240V | | | | |
| Power Factor | > 0.9 | | | | |
| Battery | LiFeP04 | | | | |
| Code W | Description | | Temp | Lm | Hours |

See end of Emergency Lighting section for spacing tables

Must be tested in line with the requirements of BS5266, failure to do so may effect battery life and warranty.

LED Emergency Non Maintained Downlight Open Area

LED Emergency Non Maintained Downlight Corridor

25000

25000

6500K

6500K

150

150