





pectrum



LED Emergency Hinged Exit Box

Our Spectrum LED Emergency Hinged Exit Box is one of our most popular emergency products. The tried and tested robust design and polycarbonate construction makes this exit box ideal for all commercial and industrial environments.

- Selectable Self Test or Manual Emergency Mode
- · Hinged for quick and easy installation and maintenance
- Tool free termination
- · Sleek, energy efficient design
- Different legend options available
- Suitable for commercial and industrial installations
- Viewing distance 25m












Auto Self Test Indicator. No requirement for manual key test (when switched to self test operation)

Normal operation: Green indicator illuminated

Battery failure: Red indicator flashes once every 3 seconds Light source failure: Red indicator flashes twice every 3 seconds

Less than rated duration time: Red indicator flashes three times every 3 seconds.



pectrum

LED Emergency Hinged Exit Box

Legend Options







09085 New (ISO) Legend Reversible Left & Right

09087 New (ISO) Legend Down

09086 New (ISO) Legend Up

Technical Specification			
Construction	Polycarbonate		
LED Chip	Samsung		
IP Rating	IP20		
Operating Temp	0°C to +35°C		
Input Voltage	220 - 240V		
Power Factor	> 0.9		
Battery	LiFeP04		

Code	W	Description	Viewing Distance	Temp	Hours
09083V2	4	LED Emergency Hinged Exit Box including Up Legend.	25M	6500K	30000
09085	_	New (ISO) Legend Reversible Left & Right (spare accessory)	-	-	_
09087	_	New (ISO) Legend Down (spare accessory)	-	-	-
09086	_	New (ISO) Legend Up (spare accessory)	-	-	_

Must be tested in line with the requirements of BS5266, failure to do so may effect battery life and warranty.

 $^{^{1}}$ Exceeds EU standard of 70 for Lumens Maintenance Ratio 2 Exceeds EU standard of Ra 80 for Colour Rendering Index

³ Subject to terms & conditions (Contact Customer Service)





technical@belllighting.co.uk sales@belllighting.co.uk