

BELLlighting

242





www.belllighting.co.uk

Spectrum


LED Emergency Hinged Exit Box

Our Spectrum LED Emergency Hinged Exit Box is one of our most popular emergency products. The tried and tested robust design and polycarbonate construction makes this exit box ideal for all commercial and industrial environments.

- Hinged for quick and easy installation and maintenance
- Tool free termination
- Sleek, energy efficient design
- Different legend options available
- Suitable for commercial and industrial installations
- IP20
- Viewing distance 25m



Auto Self Test Indicator. No requirement for manual key test (Code: 09084) Normal operation: Green indicator illuminated Battery failure: Red indicator flashes once every 3 seconds Light source failure: Red indicator flashes twice every 3 seconds Less than rated duration time: Red indicator flashes three times every 3 seconds.







LED Emergency Hinged Exit Box

Legend Options



Left & Right

Legend Down



Technical Specification				
Construction	Polycarbonate			
LED Chip	Samsung			
IP Rating	IP20			
Operating Temp	-5°C to +35°C			
Input Voltage	220 - 240V			
Power Factor	> 0.9			
Battery	LiFeP04			

Code	W	Description	Viewing Distance	Temp	Hours
09083	4	LED Emergency Hinged Exit Box including Up Legend.	25M	6500K	30000
09084	4	LED Emergency Hinged Exit Box, Self Test including Up Legend	25M	6500K	30000
09085	_	New (ISO) Legend Reversible Left & Right (spare accessory)	-	-	_
09087	_	New (ISO) Legend Down (spare accessory)	-	-	-
09086	-	New (ISO) Legend Up (spare accessory)	-	-	_

Must be tested in line with the requirements of BS5266, failure to do so may effect battery life and warranty.

¹ Exceeds EU standard of 70 for Lumens Maintenance Ratio

² Exceeds EU standard of Ra 80 for Colour Rendering Index ³ Subject to terms & conditions (Contact Customer Service)





245