ecoslim

LED CCT Bulkhead

- One of the most decorative, aesthetically pleasing bulkheads in the BELL range
- Supplied with white bezel as standard with the option to add a variety of decorative bezels
- Selectable colour temperature 3000K/4000K/6000K
- Chrome, satin, copper and antique brass trims available
- The ideal replacement for 2D and PL decorative fittings
- 8M detection range on corridor dim option (2.6m mounting height)
- Emergency option
- Microwave and corridor dimming function option
- Rear entry

12W⊜ ₩ 57	y Saving 7% 18W€	52%	5w⊜ 🐺 ^{Energy Savi} 54%		
Quality Assured Product Warranty ³	On site Warranty ³	Colour Rendering Index ³	Lumens Maintenance Ratio ¹	Water & Dust Protected	Impac Rating
5 Year	2 Year	85	L80 B10	IP54	IK8
Exc Battery	Exc Battery				


Technical Specification					
Construction	Polycarbonate				
Driver	BELL				
LED Chip	Samsung				
Input Voltage	220 - 240V				
Power Factor	> 0.9				
Operating Temp	-20°C to +35°C / Emergency version min temp -5°C				
Standard	CE & UKCA				

Optional infra-red remote control available for sensor versions	

Quick and easy adjustment for multiple fittings; dimming level, presence detection, light levels & automatic on-off time. Average 4M range.

Operating Hours 50,000







5 rear	Silver	Warranty					
Code	W	Description	Lm	Lm/W	Temp	HxØ (mm)	
06830	12	Deco Slim LED Bulkhead CCT	1056	88		48x250	
06833	12	Deco Slim LED Bulkhead CCT Emergency	1056	88	3/4/6000K		
06824	12	Deco Slim LED Bulkhead CCT Sensor On/Off	1056	88			
06827	12	Deco Slim LED Bulkhead CCT Sensor Emergency	1056	88			
06831	18	Deco Slim LED Bulkhead CCT	1620	90		48x300	
06834	18	Deco Slim LED Bulkhead CCT Emergency	1620	90	3/4/6000K		
06825	18	Deco Slim LED Bulkhead CCT Sensor On/Off	1620	90			
06828	18	Deco Slim LED Bulkhead CCT Sensor Emergency	1620	90			
06832	25	Deco Slim LED Bulkhead CCT	2150	86	- 3/4/6000K	48x300	
06835	25	Deco Slim LED Bulkhead CCT Emergency	2150	86			
06826	25	Deco Slim LED Bulkhead CCT Sensor On/Off	2150	86			
06829	25	Deco Slim LED Bulkhead CCT Sensor Emergency	2150	86			
06752	-	Satin Trim for 12W Deco Slim LED Bulkhead	-		-	-	
06753	-	Satin Trim for 18/25W Deco Slim LED Bulkhead	-	-		-	
06754	-	Chrome Trim for 12W Deco Slim LED Bulkhead	-		-	-	
06755	-	Chrome Trim for 18/25W Deco Slim LED Bulkhead	-		-	-	
06756	-	Copper Trim for 12W Deco Slim LED Bulkhead	-		-	-	
06757	-	Copper Trim for 18/25W Deco Slim LED Bulkhead	-		-	-	
06758	-	Antique Brass Trim for 12W Deco Slim LED Bulkhead	-		-	-	
06759	-	Antique Brass Trim for 18/25W Deco Slim LED Bulkhead	-		-	-	

Microwave Max Operating Height 3.2m

Tri-Level Control (Corridor Function)



With sufficient natural light, the fitting does not switch on when presence is detected.



light dims to stand-by level (10% / 20% / 30%) after the hold-time.



With insufficient natural light, the sensor switches on automatically when someone enters the room.



Offers 3 levels of light: 100%-dimmed light (10%, 20%, 30%)-off; and 2 periods of selectable waiting time: motion hold-time and stand-by period; selectable daylight threshold and choice of detection area.





Rotherham College: BELL Deco Slim LED Bulkheads

Over the life of the fittings, Rotherham College could save: £5376 in energy costs, energy saving 34%

- Annual Energy Saving 2,796kWh
- Annual CO₂ Saving 1,565kg
- Annual Maintenance £600