

SkylineELITE+

High Output Asymmetric LED Floodlight

- Genuine replacement for up to 1500W Metal Halide Floodlight
- Perfect for sports, building facades, landscape, security & car park lighting
- Asymmetric distribution, low light pollution
- 145 Lm/W
- Aerodynamic, streamlined design for reduced windage
- Fully encapsulated IP66 TUV certified driver
- Nichia GRT-V1 LED
- Fully adjustable mounting bracket
- Die-cast aluminium



600W \equiv 1500W MH Energy Saving 60%

Quality Assured Product Warranty¹
10 Year

On site Warranty¹
2 Year

Colour Rendering Index²
80

Lumens Maintenance Ratio³
L80 B10

Water & Dust Protected
IP66

Impact Rating
IK8


Surge Protected
10000V

Suitable For Site Lighting
110V

Operating Hours
70,000

Technical Specification

Construction	Polyester coated die-cast LM6 Marine Grade aluminium & toughened safety glass
Driver	Sosen (1-10V dimmable)
LED Chip	Nichia GRT-V1
Input Voltage	100 - 277V (277 - 440V special order)
Power Factor	> 0.9
Operating Temp	-30°C - +45°C
Standard	CE & UKCA





10 Year Gold Warranty

Code	W	Description	Lm	Temp	Lm/W	Weight	Windage	WxHxD (mm)
08873	600	Asymmetric Floodlight Type 2	87000	4000K	145	18Kg	0.37m ² @ 0°	
08874	600	Asymmetric Floodlight Type 3	87000	4000K	145	18Kg	0.37m ² @ 0°	601x621x104
08875	600	Asymmetric Floodlight Type 4	87000	4000K	145	18Kg	0.37m ² @ 0°	