

bellluminaslim elite

LED High Bay

- Our most energy efficient High Bay to date (up to 200lm/W)
- Wattage Switchable option available
- TUV Driver
- Seoul Semiconductor LED
- 90° & 120° lens options
- Plug-in PIR & Microwave sensors available
- Sensor parameters set by remote control
- Genuine Replacement for 400W/600W/1000W Metal Halide or Sodium
- Cool White 4000K
- High CRI Ra85
- Perfect for warehousing, large retail and factories
- Up to 200 Lm/W



100W \equiv 400 W MH/SON 75% Energy Saving

150W \equiv 600 W MH/SON 75% Energy Saving

200W \equiv 1000 W MH/SON 80% Energy Saving

Quality Assured Product Warranty¹
7 Year

On site Warranty¹
2 Year

Colour Rendering Index²
85

Lumens Maintenance Ratio³
L80 B10

Water & Dust Protected
IP65


Surge Protected
4000V

Impact Rating
IK10

Operating Hours
50,000

Technical Specification

Construction	Die Cast Aluminium
Driver	LiFud
LED Chip	Seoul Semiconductor
Input Voltage	220-240V
Power Factor	> 0.9
Operating Temp	-30°C to +35°C / Emergency version min temp -5°C
Standard	CE & UKCA





7 Year Gold Warranty

Code	W	Description	Lm	Temp	Weight	ØxH (mm)
08889	150/200	LED High Bay, Wattage Switchable 120° Lens	30000/39200	4000K	2.9Kg	364x167
08890	150/200	LED High Bay, Wattage Switchable, 90° Lens	30000/39200	4000K		
08891	150/200	LED High Bay, Wattage Switchable, 120° Lens, Emergency	30000/39200	4000K		
08892	150/200	LED High Bay, Wattage Switchable, 90° Lens, Emergency	30000/39200	4000K		