



LED CCT Wattage Switchable Integrated Batten

- Combines the reliability of the Ultra Batten with the added CCT & wattage switchable functionality
- Versatile general-purpose batten
- Plug in emergency packs, Microwave and PIR on/off sensors create a very stock friendly solution for wholesalers and contractors alike
- The ideal replacement for Single/Twin Fluorescent T8 and T5 Fixtures
- Special high light transmission frosted polycarbonate diffuser
- Tool-free termination
- Shatterproof



Quality Assured
Product Warranty¹
7 Year

On site
Warranty²
2 Year

Colour Rendering
Index³
85

Lumens
Maintenance Ratio⁴
L80 B10

Water & Dust
Protected
IP20

Impact
Rating
IK8

Operating
Hours
50,000

Technical Specification	
Construction	Steel Body, Polycarbonate lens
Driver	BELL
LED Chip	Samsung
Input Voltage	220 - 240V
Power Factor	> 0.9
Operating Temp	-30°C to +35°C / Emergency version min temp -5°C
Standard	CE & UKCA





7 Year Gold Warranty

Code	W	Description	Lm	Temp	LxHxD Fixings (mm)
10278	20/40	Integrated Batten - Wattage Switchable, CCT, 1200mm (4ft)	2850-5400	3/4/6000K	1230x82x69 290/17/320
10279	30/60	Integrated Batten - Wattage Switchable, CCT, 1500mm (5ft)	4100-7700	3/4/6000K	1530x82x69 290/170/320
10280	40/80	Integrated Batten - Wattage Switchable, CCT, 1800mm (6ft)	5350-10850	3/4/6000K	1795x82x69 415/170/320
10281	-	Plug in Emergency Pack for CCT Battens	-	-	-
10282	-	Plug in Sensor On/Off for CCT Battens	-	-	-
10293	-	Plug in PIR for CCT Battens	-	-	-
10294	-	Remote Control for CCT Battens (PIR only)	-	-	-
91359	-	Plug In Self Test pack for CCT Battens	-	-	-

PIR Max Operating Height 3.2m