

Firestayprimo

CCT 4 COLOUR / 3 WATTAGE SWITCHABLE

Integrated LED Fixed Downlight

- High Output Downlight ideal for high ceilings or any project requiring high intensity light
- Firestay Certification: 30, 60 and 90 minute solid joist ceilings, 30 minute I-Joist & Metal Web ceiling systems
- Front CCT switch
- 12 in 1 Fixture: 4 colour temperatures, 3 wattages
- White, Satin, Chrome, Brass, Antique Brass & Matt Black bezels available
- Part B / C / E compliant
- IC rated
- Tool-Free termination
- 60° Beam Angle
- Spacer plate options available




Quality Assured Product Warranty ¹ 7 Year	Colour Rendering Index ² 85	Lumens Maintenance Ratio ³ L80 B10	Water & Dust Protected IP65	I Joist Certified Fire Rated	30/60/90 Minutes Solid Joist Fire Rated	Compliant Part L	 Coverable	Operating Hours 50,000
--	--	---	---------------------------------------	--	---	----------------------------	---	----------------------------------

Technical Specification	
Construction	Die-Cast Aluminium
Driver	BELL
LED Chip	Epistar
Input Voltage	220 - 240V
Power Factor	> 0.9
Operating Temp	-5°C to +35°C
Standard	CE & UKCA



Lever Tool-Free Terminal





7 Year Gold Warranty

Code	W	Description	Lm	Temp	ØxHxBezelxCut Out Ø (mm)
11390	6/8/10	Firestay Primo LED CCT Wattage Switchable Downlight Dim, CCT, P&P, 60° Beam Angle, Lever Tool Free Termination	720 - 1170	2.7/3/4/6K	XXx52x90x70
11372	-	Satin Bezel for above	-	-	-
11373	-	Chrome Bezel for above	-	-	-
11374	-	Brass Bezel for above	-	-	-
11375	-	Antique Brass Bezel for above	-	-	-
11376	-	Matt Black Bezel for above	-	-	-
11378	-	Bright White Bezel for above	-	-	-
11369	-	White Spacer Plate for Primo/Duo/Geo	-	-	-
11368	-	Satin Spacer Plate for Primo/Duo/Geo	-	-	-
08196	-	Emergency Pack for above	-	-	-