

LED Sustainable Modular Downlight

- Patented technology has been developed to be energy saving while incorporating a fully circular economy design
- Zero land fill, 90% of all material used on this product will be re-used and re-manufactured
- Firestay Certification: 30, 60 and 90 minute solid joist ceilings, 30 minute I-Joist & Metal Web ceiling systems
- TM66 Certified (Excellent Circularity)
- 2700/3000/4000/6000K Colour selectable
- White, Satin, Chrome, Brass, Antique Brass & Matt Black bezels available
- The Geo-Mod® is dimmable
- The Geo-Mod® enables the end user to quick fix and replace the CCT LED unit at the end of product life. Simply return the Geo-Mod® as per instructions on the unit






















Technical Specification					
Construction	Die-Cast Aluminium/Recycled Polycarbonate				
Driver	BELL				
LED Chip	Epistar				
Input Voltage	220 - 240V				
Power Factor	> 0.9				
Operating Temp	-5°C to +35°C				
Standard	CE & UKCA				









7 Year Gold Warranty					
Code	W	Description	Lm	Temp	HxBezelxCut Out Ø (mm)
11391	-	Firestay Geo® LED Sustainable Modular Downlight Housing	-	-	52x90x70
11392	5.5	Firestay Geo [®] LED Sustainable, Dimmable Module - CCT	600-650	2.7/3/4/6000K	-
11372	-	Satin Bezel for above	-	-	-
11373	-	Chrome Bezel for above	-	-	-
11374	-	Brass Bezel for above	-	-	-
11375	-	Antique Brass Bezel for above	-	-	-
11376	-	Matt Black Bezel for above	-	-	-
11378	-	Bright White Bezel for above	-	-	-
11369	-	White Spacer Plate for Primo/Duo/Geo	-	-	-
11368	-	Satin Spacer Plate for Primo/Duo/Geo			



The housing has been designed to remain in the ceiling for life removing any need for recycling or possibility for landfill disposal.

The Geo-Mod $^{\scriptsize @}$ (sold separately) has been designed so at the end of life it can be returned to the manufacturer to be

re-used and re-manufactured saving the need to recycle 90% of the product.