

IP65 Backlit LED Panel


- Wattage Switchable
- IP65 LED Panel is an ideal product for areas that may contain moisture such as changing rooms, locker rooms θ commercial kitchen environments
- Front face IP65
- Professional Backlit LED panel
- 0-10V Dimming or DALI Dimming options available
- TPb
- BELL Driver

Panel Warranty³

- Anti-twist frame
- Emergency panels with 5 year battery warranty available



Technical Specification			
Construction	Steel + PMMA		
Driver	BELL		
LED Chip	Philips		
Input Voltage	220 - 240V		
Power Factor	> 0.9		
Operating Temp	0°C to +35°C		
Standard	CE & UKCA		



2 Year



Code	W	Description	Lm	Temp	WxHxD (mm)
11780	20/26/30/36	IP65 LED Backlit Panel - 600x600mm	2600-4650	4000K	- 595x595x25
11781	20/26/30/36	IP65 LED Backlit Panel - 600x600mm, Emergency (1 Year Battery Warranty)	2600-4650	4000K	
11783	36	IP65 LED Backlit Panel - 600x600mm, White, 0-10V Dim	4650	4000K	-
11784	36	IP65 LED Backlit Panel - 600x600mm, White, Dali Dim	4650	4000K	-
08747	2.5	LED Emergency Pack (self + manual test)	-	-	-
30024	-	Burgess Ceiling Grid Bracket Kit for LED Panels	-	-	-