

## LED BLD/BLT/BLL/BLS

- Energy saving benefits of LED without having to change fittings
- Aluminium heat sink for improved life
- True retrofit size
- High CRI
- Not suitable for emergency or dimming
- Suitable for switch start/magnetic control gear
- Must bypass High Frequency control gear



### 3 Year Silver Warranty

Code	Lamp Type	Temp	Lm	HxW (mm)
Non Dimmable				
70080	3.5W LED BLS 2 Pin - G23	4000K	350	135x32
70081	6W LED BLS 2 Pin - G23		600	237x32
70082	7W LED BLD 2/4 Pin - G24d/q		700	148x35
70083	9W LED BLD 2/4 Pin - G24d/q		900	171x35
70084	7W LED BLT 2/4 Pin - GX24d/q		700	124x38
70085	9W LED BLT 2/4 Pin - GX24d/q		900	139x38
70086	10W LED BLL 4 Pin - 2G11		1000	327x44
70087	18W LED BLL 4 Pin - 2G11		1800	542x44

For use with magnetic ballast: Remove starter and capacitor

For use with electronic ballast: Remove control gear and wire directly to mains

Not suitable for emergency

### Energy Savings compared to old technology CFL Lamps



Quality Assured  
Product Warranty<sup>2</sup>  
**5 Year**

Colour Rendering  
Index<sup>3</sup>  
**85**

Lumens  
Maintenance Ratio<sup>3</sup>  
**80**

Operating  
Hours  
**45,000**

