





## LED T5

Our LED T5 tubes are suitable for both switch start and high frequency and are the perfect way to replace conventional fluorescent tubes. A cost-effective energy saving solution without the need to replace a complete fitting while reaping the energy saving benefits of LED.

- Designed to replace conventional fluorescent tubes.
- Long life 45000 hours
- Low maintenance costs
- 5 Year Warranty
- Up to 49% Energy Savings



Frosted Glass

Cool White

Tube Ø 20mm

9W L 549mm

12W L 849mm

16W L 1149mm

19W L 1449mm

25W L 1449mm





## LED T5

Code	Lamp Type	CCT	Lm	Dim	V	Hours
Non Dimmable						
04338	9W LED T5 HE Tube - G5, Non Dim, 549mm	4000K	950	Non Dim	240	45000
04339	12W LED T5 HE Tube - G5, Non Dim, 849mm	4000K	1440	Non Dim	240	45000
04340	16W LED T5 HE Tube - G5, Non Dim, 1149mm	4000K	2100	Non Dim	240	45000
04341	19W LED T5 HE Tube - G5, Non Dim, 1449mm	4000K	2500	Non Dim	240	45000
04355	10W LED T5 HO Tube - 4000K, 549mm	4000K	1600	Non Dim	240	45000
04356	16W LED T5 HO Tube - 4000K, 849mm	4000K	2400	Non Dim	240	45000
04357	25W LED T5 HO Tube - 4000K, 1149mm	4000K	3800	Non Dim	240	45000
04343	25W LED T5 HO Tube - G5, Non Dim, 1449mm	4000K	3500	Non Dim	240	45000

NEW

NEW

NEW

For use with magnetic ballast: Remove starter and capacitor  
 For use with electronic ballast: Remove control gear and wire directly to mains  
 Not suitable for emergency

<sup>1</sup> Exceeds EU standard of 70 for Lumens Maintenance Ratio

<sup>2</sup> Exceeds EU standard of RA 80 for Colour Rendering Index

<sup>3</sup> Subject to terms & conditions (Contact Customer Service)

Call Customer Service or see website for maximum loading and dimmer compatibility.

