





IP65 LED Bulkhead


The Oberon IP65 LED Bulkhead is a sleek bulkhead supplied with a matt black bezel. This anti-corrosive bulkhead is suitable for BESA box mounting with the option to add a variety of interchangeable bezels.

- Anti-corrosive polycarbonate body
- Standard / Emergency Version / Microwave Version / Emergency Microwave Version
- Supplied with black bezel
- No maintenance / lamp replacement
- 8M Detection range on sensor versions
- 50000 Hours
- 20mm side, bottom & top entry
- Eyelid and louvre bezels available



LMR80: Maximum 20% of lumen depreciation over rated hours.

B10: Maximum 10% of fittings failure rate over rated hours



technical@bellighting.co.uk
sales@bellighting.co.uk



IP65 LED Bulkhead

Technical Specification	
Construction	Polycarbonate
Driver	BELL
LED Chip	Samsung
IP Rating	IP65
Operating Temp	-20°C to +35°C
Input Voltage	220 - 240V
Power Factor	> 0.9
CRI	85 - Exceeds EU standard of Ra 70 for Colour Rendering Index
LMR	80 - Exceeds EU standard of 70 for Lumens Maintenance Ratio
L1A / L1B / L2A / L2B Compliant	Yes

Code	V	W	Temp	Lm	Description	Hours
10600	220-240	20	4000K	1800	Oberon LED Bulkhead, with black bezel	50000
10601	220-240	20	4000K	1800	Oberon LED Bulkhead Emergency, with black bezel	50000
10602	220-240	20	4000K	1800	Oberon LED Bulkhead M/W Sensor, with black bezel	50000
10603	220-240	20	4000K	1800	Oberon LED Bulkhead Emergency M/W Sensor, with black bezel	50000
10607	-	-	-	-	White Bezel, (optional accessory)	-
10608	-	-	-	-	Silver Bezel, (optional accessory)	-
10609	-	-	-	-	Black Eyelid, (optional accessory)	-
10610	-	-	-	-	White Eyelid, (optional accessory)	-
10611	-	-	-	-	Silver Eyelid, (optional accessory)	-
10612	-	-	-	-	Black Louvre, (optional accessory)	-
10613	-	-	-	-	White Louvre, (optional accessory)	-
10614	-	-	-	-	Silver Louvre (optional accessory)	-

Microwave Max Operating Height 3.2m

Emergency versions must be tested in line with the requirements of BS5266, failure to do so may effect battery life and warranty.

¹ Exceeds EU standard of 70 for Lumens Maintenance Ratio

² Exceeds EU standard of RA 70 for Colour Rendering Index

³ Subject to terms & conditions (Contact Customer Service)

