



IC Rated up to 270mm insulation

www.belllighting.co.uk



Integrated LED Fixed/Tilt Downlight

The most cost effective integrated downlight in the BELL range, the Firestay Slim comes with a 3 year quality warranty. Fixed and Centre Tilt options available with a choice of finishes and colour temperatures.

- Firestay Certification: 30, 60 and 90 minute solid joist ceilings, 30 minute I-Joist & Metal Web ceiling systems
- IP65 Fixed Versions / IP44 Tilt Version
- 30/60/90 minutes firestay
- Part B/C/E compliant
- · Choice of finishes
- Dimmable
- Cut Out Ø55-68 mm
- Tool Free Connector





















LMR80: Maximum 20% of lumen depreciation over rated hours. B10: Maximum 10% of fittings failure rate over rated hours



Bezel Diameter 81.5mm Cut Out Ø 55-68mm



Cut Out Ø 55-68mm

Fixed Downlight





Tool Free Connector 2.5mm twin earth loop in / loop out push-fit connectors



Integrated LED Fixed/Tilt Downlight

Technical Specification				
Construction	Pressed Steel			
Driver	On Board			
LED Chip	Samsung			
IP Rating	Fixed IP65 / Centre Tilt IP44			
Operating Temp	-5°C to +35°C			
Input Voltage	220 - 240V			
Power Factor	> 0.9			
CRI	85 - Exceeds EU standard of Ra 80 for Colour Rendering Index			
LMR	80 - Exceeds EU standard of 70 for Lumens Maintenance Ratio			

Code	Description	Colour Temp	Lm	Beam ⁰	Hrs
10675	5W Firestay Integrated LED Fixed Downlight White Bezel	3000K	500	60°	35000
10676	5W Firestay Integrated LED Fixed Downlight White Bezel	4000K	550	60°	35000
10677	5W Firestay Integrated LED Fixed Downlight Satin Bezel	3000K	462	60°	35000
10678	5W Firestay Integrated LED Fixed Downlight Satin Bezel	4000K	550	60°	35000
10679	5W Firestay Integrated LED Fixed Downlight Chrome Bezel	3000K	462	60°	35000
10680	5W Firestay Integrated LED Fixed Downlight Chrome Bezel	4000K	492	60°	35000
10681	5W Firestay Integrated LED Centre Tilt Downlight White Bezel	3000K	450	60°	35000
10682	5W Firestay Integrated LED Centre Tilt Downlight White Bezel	4000K	478	60°	35000
10683	5W Firestay Integrated LED Centre Tilt Downlight Satin Bezel	3000K	450	60°	35000
10684	5W Firestay Integrated LED Centre Tilt Downlight Satin Bezel	4000K	478	60°	35000
10685	5W Firestay Integrated LED Centre Tilt Downlight Chrome Bezel	3000K	450	60°	35000
10686	5W Firestay Integrated LED Centre Tilt Downlight Chrome Bezel	4000K	560	60°	35000

¹ Exceeds EU standard of 70 for Lumens Maintenance Ratio ² Exceeds EU standard of RA 80 for Colour Rendering Index

³ Subject to terms & conditions (Contact Customer Service)

