Aquaendure

Wattage Switchable CCT, Vandal Resistant Anti Ligature LED Bulkhead

- Up to 130 lm/W
- CCT 3000K/4000K/6000K
- Genuine Replacement for 38W & 70W Bulkhead
- High impact polycarbonate lens
- Suitable for custodial and secure healthcare applications
- No lamp replacement
- Designed with safety as a priority






















•	100.000	
	Hours	
\cap	Operating	

Technical Specification				
Construction	Cast Aluminium + Polycarbonate			
Driver	BELL			
LED Chip	Samsung			
Input Voltage	220 - 240V			
Power Factor	> 0.9			
Operating Temp	-20°C to +40°C			
Standard	CE & UKCA			





10 Year Gold Warranty						
Code	W	Description	Lm	Temp	ØxH (mm)	
70035	18-36	Aqua Endure Anti Ligature Wattage Switchable LED Bulkhead - White	2300-4680	3/4/6000K	400x110	
70036	18-36	Aqua Endure Anti Ligature Wattage Switchable LED Bulkhead - White, Emergency Self Test On/Off Switch	2300-4680	3/4/6000K	400x110	
70037	28-36	Aqua Endure Anti Ligature Wattage Switchable LED Bulkhead - White, M/W Sensor Corridor Dim	2300-4680	3/4/6000K	400x110	
70038	28-36	Aqua Endure Anti Ligature Wattage Switchable LED Bulkhead - White, Emergency Self Test On/Off Switch, M/W Sensor Corridor Dim	2300-4680	3/4/6000K	400x110	
70039	18-36	Aqua Endure Anti Ligature Wattage Switchable LED Bulkhead - White, with 7W Nightlight (6-9W)	2300-4680	3/4/6000K	400×110	
70040	18	Aqua Endure Anti Ligature, LED Bulkhead - White, Dali	2300	3/4/6000K	400×110	
70029	36	Aqua Endure Anti Ligature, LED Bulkhead - White, Dali	4680	3/4/6000K	400×110	
*Lumens based on 4000K						