

## LED Emergency Exit Blade

- Easy switching from non maintained to maintained via removable link
- Suitable for commercial and industrial installations
- Selectable Self Test or Manual Emergency Mode
- Supplied with New Up Legend as standard
- Recessing Kit option (Code 09048)
- Can be mounted to ceiling or wall
- Maintained/Non Maintained
- Viewable from both sides
- Sleek, low profile design
- 25M Viewing Distance



Product Warranty<sup>3</sup>  
Including Battery

**5 Year**

Water & Dust  
Protected

**IP20**

Self Test or  
Manual Emergency


**Mode**

Operating  
Hours


**30,000**

Technical Specification	
Construction	Polycarbonate
LED Chip	Samsung
Input Voltage	220–240VAC, 50 / 60Hz
Power Factor	>0.9
Operating Temp	0°C to +35°C
Standard	CE & UKCA
Battery	LiFePO4


Surface Mounted Fitting



Recessed Fitting with 09048



Rotating fixing, can be mounted to ceiling or wall at 90° angle





### 5 Year Silver Warranty

Code	W	Description	Temp	Viewing Distance	WxHxD
09012V2	2.5	LED Emergency Exit Blade Surface including Up Legend. Maintained/Non Maintained	6000K	25M	310x230x35
09013	-	New Legend Left & Right for Exit Blade	-	-	-
09014	-	New Legend Down for Exit Blade	-	-	-
09015	-	New Legend Up for Exit Blade	-	-	-
09016	-	Old Legend Left & Right for Exit Blade	-	-	-
09017	-	Old Legend Down for Exit Blade	-	-	-
09018	-	Old Legend Up for Exit Blade	-	-	-
09048	-	Recessing kit for Emergency Surface Exit Blade	-	-	-

### Legend Options



09013 New (ISO)  
Left & right

09014 New (ISO)  
Legend Down

09015 New (ISO)  
Legend Up



09016 Old (Euro) Legend  
Left & Right

09017 Old (Euro)  
Legend Down

09018 Old (Euro)  
Legend Up