


LED Integrated CCT UGR<19 Batten

- 36 in 1 fitting with plug-in emergency packs, Microwave and PIR on/off sensors available, along with a DALI-2 Dimming version
- Special high light transmission frosted polycarbonate diffuser for smooth uniform lighting with reduced glare
- Perfect for schools, universities & hospitals where a flexible wattage and selectable colour batten is required
- The ideal replacement for Single/Twin Fluorescent T8 and T5 Fixtures
- Colour switchable with a choice of 3000K/4000K/6000K
- Suitable for food environments
- Tool-free termination
- Shatterproof
- Suitable for surface mounting



| | | | | | | | |
|--|--|--|---|---------------------------------------|------------------------------|---|----------------------------------|
| Quality Assured Product Warranty ² 7 Year | On site Warranty ³ 2 Year | Colour Rendering Index ² 80 | Lumens Maintenance Ratio ² L80 B10 | Water & Dust Protected IP40 | Impact Rating IK08 | Low Unified Glare Rating UGR <19 | Operating Hours 50,000 |
|--|--|--|---|---------------------------------------|------------------------------|---|----------------------------------|

| Technical Specification | |
|-------------------------|---|
| Construction | Steel Body / Polycarbonate Diffuser |
| Driver | Tridonic |
| LED Chip | Samsung |
| Input Voltage | 220–240VAC, 50 / 60Hz |
| Power Factor | >0.9 |
| Operating Temp | -20°C to +35°C (Emergency version min temp 0°C) |
| Standard | CE & UKCA |





7 Year Gold Warranty

| Code | W | Description | Lm | Temp | LxHxD (mm) |
|-------------------------------|--------------|---|-----------|-----------|-------------|
| 10285V2 | 20/27/33/38W | Wattage Switchable LED Batten CCT, 1200mm (4ft) | 2670-5140 | 3/4/6000K | 1205x97x200 |
| 10286V2 | 25/34/40/48W | Wattage Switchable LED Batten CCT, 1500mm (5ft) | 3270-6480 | 3/4/6000K | 1505x97x200 |
| 10281 | - | Plug-in Emergency Pack for above | - | - | - |
| 10282 | - | Plug-in Microwave Sensor On/Off for above | - | - | - |
| 10293 | - | Plug-in PIR for above | - | - | - |
| 08673 | - | Remote Control for CCT Battens (PIR only) | - | - | - |
| 91359 | - | Plug-in Self Test pack for CCT Battens | - | - | - |
| PIR Max Operating Height 3.2m | | | | | |
| Lumens based on 4000K | | | | | |