




LED Single/Switchable Wattage, CCT Downlight

- Arial Pro can be installed in a variety of applications with the confidence of knowing this product will stand the test of time
- Sleek looking luminaire designed to replace cumbersome CFL fittings
- Emergency downlights with 5 year battery warranty available
- Ideal for changing rooms, toilets & reception environments
- Switchable colour temperature 3000K/4000K/6000K
- Equivalent up to 2x26W fluorescent
- IP44 and IP65 options available
- Tool Free - Plug & Play
- Low glare
- TPa



Quality Assured Product Warranty ² 7 Year	On site Warranty ³ 2 Year	Battery Warranty ¹ Emergency Versions 1 Year	Colour Rendering Index ² 80	Lumens Maintenance Ratio ² L80 B10	Water & Dust Protected IP65	Water & Dust Protected IP44	Operating Hours 50,000
--	--	---	--	---	---------------------------------------	---------------------------------------	----------------------------------

Technical Specification	
Construction	Polycarbonate
Driver	BELL
LED Chip	Philips
Input Voltage	220-240VAC, 50 / 60Hz
Power Factor	>0.9
Operating Temp	-20°C to +35°C (Emergency version min temp 0°C)
Standard	CE & UKCA



7 Year Gold Warranty					
Code	W	Description	Lm	Temp	ØxHxCut Out (mm)
10950	6/8/10	Arial Pro LED Downlight IP44	570-1050		115x70x90
10951	12/16	Arial Pro LED Downlight IP44	1200-1850		190x102x160
10952	12/16/18/20	Arial Pro LED Downlight IP44	1350-2400		240x117x200
10956	6/8/10	Arial Pro LED Downlight IP44 - Emergency (1 Year Battery Warranty)	570-1050	3/4/6000K	115x70x90
10957	12/16	Arial Pro LED Downlight IP44 - Emergency (1 Year Battery Warranty)	1200-1850		190x102x160
10958	12/16/18/20	Arial Pro LED Downlight IP44 - Emergency (1 Year Battery Warranty)	1350-2400		240x117x200
10959	10	Arial Pro LED Downlight IP44 - 1-10V Dim	1050		115x70x90
10960	16	Arial Pro LED Downlight IP44 - 1-10V Dim	1850		190x102x160
10961	20	Arial Pro LED Downlight IP44 - 1-10V Dim	2400		240x117x200
10962	10	Arial Pro LED Downlight IP44 - DALI-2 Dim	1050	3/4/6000K	115x70x90
10963	16	Arial Pro LED Downlight IP44 - DALI-2 Dim	1850		190x102x160
10964	20	Arial Pro LED Downlight IP44 - DALI-2 Dim	2400		240x117x200
10953	6/8/10	Arial Pro LED Downlight IP65	570-1050		115x70x90
10954	12/16	Arial Pro LED Downlight IP65	1200-1850		190x102x160
10955	12/16/18/20	Arial Pro LED Downlight IP65	1350-2400		240x117x200
10965	6/8/10	Arial Pro LED Downlight IP65 - Emergency (1 Year Battery Warranty)	570-1050	3/4/6000K	115x70x90
10966	12/16	Arial Pro LED Downlight IP65 - Emergency (1 Year Battery Warranty)	1200-1850		190x102x160
10967	12/16/18/20	Arial Pro LED Downlight IP65 - Emergency (1 Year Battery Warranty)	1350-2400		240x117x200
10968	10	Arial Pro LED Downlight IP65 - 1-10V Dim	1050		115x70x90
10969	16	Arial Pro LED Downlight IP65 - 1-10V Dim	1850		190x102x160
10970	20	Arial Pro LED Downlight IP65 - 1-10V Dim	2400		240x117x200
10971	10	Arial Pro LED Downlight IP65 - DALI-2 Dim	1050	3/4/6000K	115x70x90
10972	16	Arial Pro LED Downlight IP65 - DALI-2 Dim	1850		190x102x160
10973	20	Arial Pro LED Downlight IP65 - DALI-2 Dim	2400		240x117x200
08747V2	-	Arial5 Year Emergency Pack - Self Test/Non Self Test			-
09156	-	DALI-2 Self Test/Non Self Test 10-300V Emergency Pack			-

Lumens based on 4000K