

luminaLinear

LED High Intensity UGR < 20 High/Low Bay

- Ideal for racking, warehouse, large retail and factories
- Suitable for High Bay & Low Bay applications 4-12m
- Perfect for sports halls, tennis, cricket or badminton
- Genuine replacement for 400W Metal Halide
- Sensor parameters set by remote control
- Perfect for when low glare is required
- Emergency options available
- TUV Isolated Driver

CASAMBI




50W \equiv 100W Energy Saving 50%	100W \equiv 250W Energy Saving 60%	200W \equiv 400W Energy Saving 50%						
Quality Assured Product Warranty ² 7 Year	On site Warranty ² 2 Year	Colour Rendering Index ² 80	Lumens Maintenance Ratio ² L80 B10	Water & Dust Protected IP65	Surge Protected 4000V	Impact Rating IK08	Low Unified Glare Rating UGR <20	Operating Hours 50,000

Technical Specification	
Construction	Aluminium
Driver	Sosen
LED Chip	Seoul
Input Voltage	110-264VAC, 50 / 60Hz
Power Factor	>0.9
Operating Temp	-20°C to +35°C (Emergency version min temp -5°C)
Standard	CE & UKCA


Optional infra-red remote control available for microwave sensor versions.

Quick and easy adjustment for multiple fittings; dimming level, presence detection, light levels & automatic on-off time. Average 15m range







3 Step Dimming Function




With sufficient natural light, the fitting does not switch on when presence is detected.



With insufficient natural light, the sensor switches on automatically when presence is detected.



After the hold-time, the sensor dims the fitting to the pre-set low light level if no motion is detected.



Fitting switches off after the stand-by period has elapsed if no motion is detected.

7 Year Gold Warranty

Code	W	Description	Lm	Temp	Weight	LxHxW (mm)
11300	50	High Bay - Asymmetric	6692	4000K	2.3Kg	434x113x129
11301	50	High Bay - Symmetric	6860			
11306	100	High Bay - Asymmetric	12876	4000K	3.8Kg	722x113x129
11307	100	High Bay - Symmetric	13764			
11318	200	High Bay - Asymmetric,	25482	4000K	6.7Kg	1241x113x129
11319	200	High Bay - Symmetric	27388			
15189	-	Casambi PIR	-	-	-	-
15191	-	Casambi Microwave Sensor	-	-	-	-
11324	-	Suspension Kit for Illumina Linear UGR LED High Bay	-	-	-	-
11325	-	60° Adjustable Bracket	-	-	-	-
06772	-	Remote Control for above sensor versions	-	-	-	-
11449	-	Emergency Pack	-	-	-	-