



LED Wallpack CCT

- Genuine replacement for 70W Metal Halide & Sodium
- High impact polycarbonate construction
- 68% energy saving
- 30,000 hours
- 20mm side & rear entry conduit

Options

- Microwave / Emergency Microwave version
- Photocell / Emergency Photocell version
- Emergency version

CASAMBI



22W \equiv 70W Energy Saving 68%

Quality Assured
Product Warranty²
3 Year

On site
Warranty³
1 Year

Colour Rendering
Index⁴
80

Lumens
Maintenance Ratio⁵
L80 B10


Water & Dust
Protected
IP65

Impact
Rating
IK08

Operating
Hours
30,000

Technical Specification

Construction	Polycarbonate Base & Lens
Driver	BELL
LED Chip	Samsung
Input Voltage	220–240VAC, 50 / 60Hz
Power Factor	>0.9
Operating Temp	-20°C to +35°C (Emergency version min temp 0°C)
Standard	CE & UKCA





3 Year Silver Warranty

Code	W	Description	Lm	Temp	Lm/W	Weight	WxHxD (mm)
11350	16/18/20/22	Muro CCT LED Wallpack					
11351	16/18/20/22	Muro CCT LED Wallpack Emergency					
11352	16/18/20/22	Muro CCT LED Wallpack Microwave Sensor					
11353	16/18/20/22	Muro CCT LED Wallpack Photocell	1250-1750	3/4/6000K	81	1.1Kg	255x305x101
11354	16/18/20/22	Muro CCT LED Wallpack Emergency Microwave Sensor					
11355	16/18/20/22	Muro CCT LED Wallpack - Emergency Photocell					

Lumens based on 4000K