



## Wattage Switchable CCT LED Wallpack

- Genuine replacement for 70W Metal Halide & Sodium
- Asymmetric light distribution to reduce light spill
- 4 Wattage Switchable 14W/17W/21W/24W
- High impact polycarbonate lens
- CCT 3000K/4000K/6000K
- TUV Certified Driver
- 65% energy saving
- 50,000 hours

### Options

- Emergency Photocell
- Emergency
- Photocell
- Standard

CASAMBI



24W  $\equiv$   $\frac{70}{W}$  Energy Saving 65%

Quality Assured  
Product Warranty<sup>2</sup>  
**7 Year**

On site  
Warranty<sup>3</sup>  
**2 Year**

Colour Rendering  
Index<sup>2</sup>  
**80**

Lumens  
Maintenance Ratio<sup>1</sup>  
**L80 B10**



Water & Dust  
Protected  
**IP65**

Impact  
Rating  
**IK08**

Operating  
Hours  
**50,000**

### Technical Specification

Construction	Polycarbonate Base & Lens
Driver	Boke
LED Chip	Samsung
Input Voltage	220–240VAC, 50 / 60Hz
Power Factor	>0.9
Operating Temp	-20°C to +35°C (Emergency version min temp 0°C)
Standard	CE & UKCA



technical@belllighting.co.uk  
sales@belllighting.co.uk



### 7 Year Gold Warranty

Code	W	Description	Lm	Temp	Lm/W	Weight	WxHxD (mm)
70120	14/17/21/24	Wattage Switchable Asymmetric CCT LED Wallpack	1781-3241	3/4/6000K	122-157	1.15Kg	309x217x162
70122	14/17/21/24	Wattage Switchable Asymmetric CCT LED Wallpack - Photocell					
70124	14/17/21/24	Wattage Switchable Symmetric CCT LED Wallpack	1702-3071	3/4/6000K	118-134	1.15Kg	309x217x162
70126	14/17/21/24	Wattage Switchable Symmetric CCT LED Wallpack - Photocell					
70201	-	Plug-in Emergency Pack for Aqua Connect LED Bulkhead & Lumo2 CCT Wallpack - Self-Test Selectable	-	-	-	-	-

Lumens based on 4000K