



## LED Wattage Switchable CCT Bulkhead

- Impact resistant polycarbonate lens with high transmission frosted diffuser
- 8M detection range on corridor dim option (2.6m mounting height)
- Sensor has built-in with both On/Off & Corridor Dim functionality
- Available with Plug-in Emergency Pack with Self Test Switch & Microwave Sensor (optional)
- 20mm side & rear entry conduit
- Hinged LED gear tray for ease of maintenance
- Black Bezel & White/Black Eyelids available
- 3 wattage switchable 9W/12W/16W
- CCT 3000K/4000K/5000K/6000K
- Twist & Lock diffuser mechanism



Technical Specification	
Construction	Polycarbonate body and lens
Driver	BELL
LED Chip	Samsung
Input Voltage	220-240VAC, 50 / 60Hz
Power Factor	>0.9
Operating Temp	-20°C to +35°C (Emergency version min temp 0°C)
Standard	CE & UKCA





### 7 Year Gold Warranty

Code	W	Description	Lm	Temp	ØxH (mm)
70200	9/12/16	4 CCT Wattage Switchable Bulkhead	1080-2240	3/4/5/6000K	325x75
70201	-	Self-Test Selectable Emergency Pack for Aqua Connect	-	-	-
70202	-	Aqua Connect Plug-in Dual On/Off & Corridor Dim Sensor	-	-	-
70203	-	IR Remote Handset for 70202	-	-	-
70204	-	White Eyelid for above	-	-	-
70205	-	Black Eyelid for above	-	-	-
70206	-	Black Bezel for above	-	-	-

Lumens based on 4000K