



# Foxbridgesensor

## IP65 Wall/Ceiling Mount PIR Sensor

- Ease of Maintenance - the lux & time settings can be changed using potentiometers
- Adjustable head - angle of the detector head adaptable to on-site environment
- Versatile mounting options - ceiling and wall
- Wide detection angle up to 180°



Installation Height: 1.8m-2.5m



Detection Distance: Max. 12m

### 5 Year Silver Warranty

Code	Description	HxWxD (mm)
70403	IP65 Wall/Ceiling Mount PIR Sensor - White	130x80x40
70404	IP65 Wall/Ceiling Mount PIR Sensor - Black	

Quality Assured Product Warranty <sup>3</sup> <b>5 Year</b>	Water & Dust Protected <b>IP65</b>	Sensing <b>PIR</b>	Mounting Options <b>Wall/Ceiling</b>
----------------------------------------------------------------	---------------------------------------	-----------------------	-----------------------------------------

Technical Specification	
Construction	Polycarbonate Flame Retardant Body, ABS
Input Voltage	200-220 VAC
Frequency	50/60 Hz
Operating Temp	-20°C to +35°C
Load Capacity	LED 300W Halogen 1200W
Time Delay	10s-15m
Lux Settings	<3-2000Lux
Protection Class	Class II
Standard	CE & UKCA

