

Foxbridgesensor

IP20 2 in 1 Recessed/Surface Mount PIR Sensor

- Easy to change lux & time delay settings via potentiometers on the front bezel
- Compact & flat lens design for seamless integration with ceilings
- High sensitivity optics for precise detection
- Versatile mounting - Recessed & Surface



Cut Out Ø73mm (Recessed Mount)

Surface Mount



Recessed Mount

Installation Height: 2.2m-4m



SENSOR CEILING



SENSOR CEILING FLUSH



Detection Distance: Max. 8m

5 Year Silver Warranty

Code	Description	ØxD (mm)
70406	IP20 2 in 1 Recessed/Surface Mount PIR Sensor	93x35.5

Quality Assured Product Warranty ¹ 5 Year	Water & Dust Protected IP20	Sensing PIR	Mounting Options Recessed/Surface
--	---------------------------------------	-----------------------	---

Technical Specification	
Construction	Polycarbonate Flame Retardant Body, ABS
Input Voltage	200-220 VAC
Frequency	50/60 Hz
Operating Temp	-20°C to +35°C
Load Capacity	LED 400W Halogen 800W
Time Delay	10s-7m
Lux Settings	<10-2000lux
Protection Class	Class II
Standard	CE & UKCA

