

AXIOM

Wiring Accessories

INSTALLATION / OPERATING INSTRUCTIONS FOR 24 HOUR MECHANICAL SOCKET BOX TIMER - FT 24H

Please read the instructions fully
before attempting installation.


IMPORTANT

*This unit should be installed to current
IEE wiring regulations if in doubt
consult a qualified electrician.*

- Timer must not be mounted on a flammable surface.
- Ensure that the timer does not come into contact with any combustible materials such as towels or bedding.
- Ensure at least a 300mm air space is allowed around the timer.

INSTALLATION

- Prepare cable ends for connection to terminals.
- Remove the 2 screws holding the timeswitch cover to the backplate. Remove cover leaving the timeswitch hanging loose by its connection wires to the backplate.
**DO NOT INTERFERE WITH THESE
FIXED CONNECTIONS.**



WIRING

- Connect all earth wires to earthing point in wall box.
- Mount the backplate of timer to the wall box and connect the wiring as below.

CONNECTION FOR 230V SWITCHED OUTPUT

- N - Neutral
- Not Used - Not Used
- L - Live
- L Out - Live Output

**IMPORTANT: Ensure all Terminal screws
are fully tightened.**

- When the wiring is complete screw the backplate to the fitted wall box using two 3.5mm screws.
- Push the timeswitch back in to its seating on the backplate, taking care that all the wires are tucked in. Fit the cover and tighten the two screws.

SETTING THE CLOCK

- Turn the dial in the direction of the arrow (clockwise) until the correct time of day is exactly opposite time set marker ▲ on the clock face. (24 hour clock).
- For the "ON" period push the switching riders out towards the outside edge of the face. The timer will operate for the duration set (each segment is approximately 15 minutes duration). i.e. If it is required to switch on between 16.00 and 18.00, all the segments between these times should be moved to the outer edge.

SETTING THE PROGRAMME

- By moving the switch located centre right of the dock face the following operations can be achieved.
I = Permanently ON.
⌚ = Switching programme as set on dial.

TECHNICAL DATA

Switching Capacity: 230V AC, 16A resistive, 50Hz
2A Inductive

GUARANTEE

Your CED 24 Hour Mechanical
Socket Box Timer is guaranteed for
12 months from the date of purchase.
This does not affect your statutory rights.

CE INFORMATION

ACTION TYPE: IB

POLLUTION SITUATION: NORMAL

CLASS 2 INSULATION:

: MICRO-DISCONNECTION LIVE
POLE ONLY

**PLEASE KEEP THESE INSTRUCTIONS
SAFE FOR FUTURE REFERENCE**

AXIOM
Wiring Accessories

www.ced-elec.co.uk

CE

FT 24H

Size: 130(W) x 275(H)mm

Paper Material: 100P單粉紙

Print Color: K100