List No. SB639

APPLEBY SERVICE ITEMS

Circular Dry Lining Installation Box with 2 x 20mm Knockouts 35mm



- Made from flame retardant thermoplastic
- Tough yellow nylon lugs have large bearing faces for superior strength
- Large flange around the front matches profile of accessory front plates and prevents slipping into the cavity
- 25mm base knockout plus 2 side cable entry points.
- Appropriate for fitting board thicknesses from 6.35-15mm

Product Specification Data	Revision Date: 15/10/2021
CE Conformity	Yes
UKCA Conformity	Yes
Mounting method	Flush mounted (plaster)
Shape	Oval
Construction type	Device connection box (round/square)
Model	Single
Diameter	80 mm
Depth	36 mm
Internal depth	35 mm
For number of electric fittings	1
Mounting switching equipment	Screwing
With screws	No
Material	Plastic
Halogen free	No
Surface protection	Untreated
Colour	White
Degree of protection (IP)	Other
Cover model	Other
Cover attachment	Screwed

Although every effort has been made to ensure accuracy in the compilation of the technical detail within this datasheet, specifications and performance data are constantly changing. Latest details can be obtained from the Electrium website.

Electrium Sales Limited, Walkmill Lane, Cannock WS11 0XE
01543 455000 www.electrium.co.uk info@electrium.co.uk